



Different **Power Solutions**

At Tecnoware we have been designing and creating Products and Solutions for the *electric continuity of Individuals, Businesses and Industries since 1986*, using the most advanced technologies in compliance with the Environment and Safety.

Building fruitful relationships with our *Partners*, is the core of our *Company Mission*, guaranteeing mutual growth and the continuous improvement of the *professionalism* of our services and the *quality of our products*.

At Tecnoware we invest in training our *Employees*, recognising that the quality of the work and the customer satisfaction depend on the *Company's Well-being*.

Tecnowares *Environmental Sensitivity* has translated in the so-called " *Together On*" philosophy, which motivates, pushes and inspires our Stakeholders towards more and more Eco sustainable choices.

The enthusiasm and commitment of our company increase together with our successes and strengthen *the loyalty to the values* which conquered the confidence of our Partners during our Corporate History.

Tecnoware has been manufacturing UPS for private individuals, companies and industry **since 1986**.



Together on

Together On Philosophy: High **efficiency**, 100% materials **Recyclable**, **Sustainable** Development Projects.

Over 70 controls and use of **components first choice** to guarantee products up to 5 years




Branches and Partners in
50 Countries in the World.

PARTNERS AT THE CENTER



Training, Webinar,
Digital Comunication and Events.

Personal Configurator Service:
a Partner support through
guided configurations by our professionals.





24/7 Technical / Commercial Support, Shipping in 24 hours,
Configurations in 30 minutes and Installations and maintenance On-site.



UPS Technology

According to the standard regulation: IEC 62040-3, UPS are classified and identified as follows:



Electric phenomenon and solutions

UPS	Blackout	Dynamic Undervoltage	Dynamic Overvoltage	Undervoltage	Overvoltage	Lightning (Affecting a discharger upstream)	Voltage Surge	Frequency Variation	Voltage Distortion	Voltage Harmonic
Era PLUS DC - USB 5VDC 2A, USB-C OUTPUT 5V/9V/12V/15V/20V										
Era Plus DC 9 Vdc/12 Vdc - POE 24Vdc/48Vdc - USB 5Vdc										
Era Plus Strip 1.000 (VI)										
Era Plus RM 1.200 (VI)										
Era Plus 600-800-950-1.200-1.600-2.100-2.600 (VI)										
Era Plus Active 1.200-1.600 (VI)										
Exa Plus 1.100-1.600-2.100-3.000-4.500 (VI)										
Evo DSP Plus 1.200-2.400-3.600-5.500 PF 0,9 (VFI)										
Evo DSP Plus 1.200-2.400-3.600 Rack Tower PF 0,9 (VFI)										
Evo DSP Plus 6.0-10.0 PF 1 (VFI)										
Evo DSP Plus 6.0-10.0 Rack Mount PF 1 (VFI)										
Evo DSP Plus Modular 20.0-300.0 400 Vac PF 1 (VFI)										
Evo DSP Plus Modular 20.0-140.0 208 Vac PF 1 (VFI)										
Evo DSP Plus Modular 70.0-700.0 480 Vac PF 1 (VFI)										
Evo DSP Plus TM 10.0-20.0 PF 1 (VFI)										
Evo DSP Plus TT 10.0-20.0-30.0 PF 1 (VFI)										
Evo DSP Plus TT 40.0-60.0 PF 1 (VFI)										
Evo DSP Plus TT 80.0-100.0-120.0-160.0-200.0-240.0-300.0 PF 1 (VFI)										

SUMMARY

UPS

UPS Era PLUS DC - USB 5VDC 2A, USB-C OUTPUT 5V/9V/12V/15V/20V Together on	NEW	Pag.	8
UPS Era Plus DC 9VDC/12VDC - POE 24VDC/48VDC - USB 5VDC Together on		Pag.	9
Line Interactive (VI)			
UPS Era Plus Strip 1.000 Together on		Pag.	10
UPS Era Plus 1.200 Rack Mount Together on		Pag.	11
UPS Era Plus 600-800-950-1.200-1.600 Together on		Pag.	12
UPS Era Plus 2.100-2.600 Together on		Pag.	14
UPS Era Plus Active 1.200-1.600 Together on		Pag.	16
Line Interactive Sinewave (VI)			
UPS Exa Plus 1.100-1.600-2.100 Together on		Pag.	17
UPS Exa Plus 3.000-4.500 Together on		Pag.	18
On Line (VFI)			
UPS Evo DSP Plus 1.20 0-2.400-3.600-5.500 PF 0,9 Together on		Pag.	20
UPS Evo DSP Plus 1.200-2.400-3.600 Rack Tower PF 0,9		Pag.	22
UPS Evo DSP Plus 6.0-10.0 PF 1 Together on	NEW	Pag.	24
UPS Evo DSP Plus 6.0-10.0 Rack Mount PF 1 Together on	NEW	Pag.	26
UPS Evo DSP Plus Modular 20.0-300.0 400 Vac PF 1 Together on		Pag.	28
UPS Evo DSP Plus Modular 20.0-140.0 208 Vac PF 1 Together on	NEW	Pag.	30
UPS Evo DSP Plus Modular 70.0-700.0 480 Vac PF 1 Together on	NEW	Pag.	32
UPS Evo DSP Plus TM 10.0-20.0 PF 1 Together on	NEW	Pag.	34
UPS Evo DSP Plus TT 10.0-20.0-30.0 PF 1 Together on	NEW	Pag.	36
UPS Evo DSP Plus TT 40.0-60.0 PF 1 Together on	NEW	Pag.	38
UPS Evo DSP Plus TT 80.0-100.0-120.0-160.0-200.0-240.0-300.0 PF 1 Together on	NEW	Pag.	40
UPS Evo DSP Plus TT 10-20 208 Vac PF 1 Together on	NEW	Pag.	42
UPS Evo DSP Plus TT 30-40 208 Vac PF 1 Together on	NEW	Pag.	43

UPS Accessories

ATS (Automatic Transfer Switch) 16-30A		Page	44
Power Battery 12V 5Ah-7.2Ah-9Ah-54W NEW		Pag.	45

Software and communication interfaces

	Page	46
--	------	----

Stabilizers

Stabilizers Power Reg 1.000 Together on		Page	48
Stabilizers Power Reg 2.000-3.000 Together on		Pag	49
Single-Phase stabilizers with electronic control 4.5-18 Together on		Page	50
Three-Phase stabilizers with electronic control 15-100 Together on	NEW	Page	51
Bidirectional Single-Phase stabilizers with electronic control 7.5-10 Together on	NEW	Page	52

Generator

Silent Inverter Generator 2.200 Together on		Page	53
Gasoline Generator 3.200-4.200-7.800-9.200 NEW		Pag	54

Generator Accessories

Gasoline Generator ATS 45A		Page	55
----------------------------	--	------	----

Inverter

ATA Solar Inverter 1.200-3.500-5.500		Pag	56
--------------------------------------	--	-----	----



Together on

People protecting the Planet **Together**

**Help us to help
the environment!**

Tecnaware has always been a company sensitive to environmental issues. **On the 22nd April 2019**, World Earth Day, we created a new corporate philosophy called **“Together On”**. An ideal that translates into a concrete path to make our reality a 100% Green Company. ISO 14001 Certification, Green Energy, Eco-sustainable products and Packaging, Sustainable Development projects are just some of the objectives achieved.

Together On products, we turn on our focus to efficiency and sustainability

The Together On products are designed and developed with the aim of minimizing environmental impact as much as possible, improving energy efficiency, and investing in the sustainability of the production process.

● ECO-FRIENDLY PACKAGING AND COMMUNICATION:

The care for the **environment** is an integral part for the choice of our **packaging** as well as the sensitivity in leading our users towards the **proper waste disposal** for both products and packaging.

Cardboard product box

Paper tape closing

Instructions with symbols for the proper disposal of each material

UPS ERA PLUS 800 SCHUKO TOGETHER ON

Codice: FGCEBAPL8025CH
Codice EAN: 8026475175755

Le informazioni sottostanti sono solamente a scopo indicativo, si prega di fare riferimento alle indicazioni del proprio comune per un corretto smaltimento

SCATOLA DI CARTONE
Cartone ondulato (PAP-20)
Raccolta Carta

ANGOLARI IN POLISTIROLO
Polistirolo (PS-06)
Raccolta Plastica

SACCHETTO DI PLASTICA
Polietilene a bassa densità (PE-LD-04)
Raccolta Plastica

www.tecnaware.com

QR CODE label which redirect to the site

Together on

100% RECYCLABLE

Con Tecnaware a tutela dell'ambiente.
Safeguard the environment with Tecnaware.

ETICHETTA AMBIENTALE DIGITALE

ENVIRONMENTAL DIGITAL LABEL

CONSULTA LE ISTRUZIONI PER LA CORRETTA RACCOLTA DIFFERENZIATA DELL'IMBALLAGGIO
CHECK THE INSTRUCTIONS FOR THE CORRECT PACKAGING RECYCLING

www.tecnaware.com/togetheron

Together on

Con Tecnaware a tutela dell'ambiente.
Safeguard the environment with Tecnaware.

QR CODE label which redirect to the site

EN

- Fare la raccolta differenziata
- Ridurre i rifiuti
- Evitare lo spreco di energia elettrica
- Riutilizzare i contenitori in plastica
- Limitare il consumo di acqua
- Ottimizzare l'uso dei mezzi di trasporto
- Preferire imballi riutilizzabili
- Scegliere tessuti naturali
- Scegliere prodotti a km zero
- Staccare la presa degli elettrodomestici inattivi
- Fare un orto in giardino/balcone

Eco Tips and suggestions on the correct disposal of waste, contained within the packaging of each product

EN

- Separate recycling waste
- Reduce waste
- Avoid wasting electricity
- Reuse plastic containers
- Limit water consumption
- Optimize the use of transport means
- Prefer reusable packaging
- Choose natural fabrics
- Choose products at zero km
- Disconnect the plug for inoperative appliances
- Do an home vegetable garden

PAGE 6

• WEB SITE:


Our commitment to a “Green” approach is showcased on our [website](#) through a dedicated section featuring stories about **Together On** branded projects and products, as well as tips and advice on how “**To be eco-friendly**” at Home, in the Office, or while Traveling.



To be eco-friendly a Casa



To be eco-friendly in Ufficio



To be eco-friendly in Viaggio

• CERTIFICATIONS:

To be a Green Oriented company means committing to concretely reduce the production processes, storage and marketing of products impact and using clean energy sources. For this reason Tecnoware has received the **14001 Certification** and uses only **certified Green Energy**.



RePower electricity
2021 origin Certificate




RePower electricity
2022 origin Certificate



RePower electricity
2023 origin Certificate

We are engaged in telling and sharing Projects and Initiatives that allows our **Company** to be **Green-Oriented**. Concrete actions, discussion opportunities, situations to be shared along a virtuous way in **protecting and safeguarding environment direction**.



① On/off button ② Battery mode indicator ③ Line mode indicator ④ USB Type-A 5V/2A Output ⑤ USB Type-C QC/PD Output ⑥ AC Input

Main Specifications

- For powering devices such as WiFi, Routers, Modems, VOIP, cameras and charging Tablets, SmartPhones, Bluetooth headsets, Smartwatches, ecc
- 5.200 mAh Lithium-ion batteries
- Included 4 connectors: compatibility with most devices
- DC 12V 100cm output cable for connection to modem/router
- Overload and Short circuit protection
- Oversupply protection
- Temperature control inside

Specifications



UPS Model	ERA PLUS DC - USB 5VDC 2A, USB-C OUTPUT 5V/9V/12V/15V/20V
Code	FGCERAPLDC253C
Nominal Power	25 W Max
Technology	Switching with Lithium-ion batteries
Cooling	Natural
Audible noise	< 40 dBA at 1 m
Input connections	2 PIN Italy plug AC Input cable
Output connections	USB Type-C - USB Type-A
Dimensions (UPS) WxHxD	7,6x3,2x9,3cm
Dimensions (with packing) WxHxD	9,3x4,2x13,5xcm
Weight	0,5 Kg
Included	AC Input cable -100cm length - USB Type-C to 5,5x2,5mm connector - 12V 3 connectors (3,5x1,35mm - 4,8x1,7mm - 5,5x2,1mm)
Input	
Nominal voltage	Single-phase 230Vac
Input voltage range	110-240Vac
Nominal frequency	50/60 Hz
Output	
USB Type-A port	5V/2A
USB Type-C port	5V/5A - 9V/2,77A - 12V/2,08A - 15V/1,66A - 20V/1,25A
Overload capability	< 130%
Transfer time	0 ms
Battery	
Type	ICR 18650 - 3.7Vdc - 2.600 mAh x2
Capacity	3.7Vdc - 5.200 mAh - 20Wh
Backup time (typical)	240 min
Environmental specification	
Working temperature	From 0 to 45 °C (recommended from 20 to 25 °C)
Humidity	< 95% without condensation
Maximum altitude	3000 m
IP protection	IP20
Certifications	CE

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Easily replaceable batteries



Included





24V - 48V
POE

10
CONNECTORS
INCLUDED

8.800
mAh

① Line/Battery mode indicator ② On/off button ③ 12Vdc output indicator ④ 9Vdc output indicator ⑤ Battery Level indicator ⑥ 5Vdc 1A USB Charger
 ⑦ 24Vdc/48Vdc POE Output selector ⑧ LAN Input ⑨ LAN and POE Output ⑩ POE Reset ⑪ 9Vdc/12Vdc DC Output ⑫ 9Vdc/12Vdc DC Output selector
 ⑬ AC Input

Main Specifications

- For powering devices such as WiFi, Routers, Modems, VOIP, cameras and charging Tablets, SmartPhones, Bluetooth headsets, Smartwatches, ecc.
- 8.800 mAh Lithium-ion batteries
- POE function: for additional power supply on the LAN cable



- Included 10 connectors: compatibility with most devices
- Overload and Short circuit protection
- Oversupply protection
- Temperature control inside

Specifications

UPS Model	ERA PLUS DC 9VDC/12VDC - POE 24VDC/48VDC - USB 5VDC
Code	FGCERAPLDC252
Nominal Power	25 W Max
Technology	Switching with Lithium-ion batteries
Cooling	Natural
Audible noise	< 40 dBA at 1 m
Input connections	2 PIN Italy plug AC Input cable
Output connections	DC 5,5x2,5 mm - RJ45 - USB
Dimension (UPS) WxHxD	16x2,8x10,5cm
Dimension (with packing) WxHxD	17x3,5x14cm
Weight	0,5 Kg
Included	AC Input cable - DC output cable with 5,5x2,5 mm 2 connectors - 8 connectors
Input	
Nominal voltage	Single-phase 230Vac
Input voltage range	110-240Vac
Nominal frequency	50/60 Hz
Output	
POE ports	24Vdc/48Vdc (selectable) 0.6A max, +Pin 4/5, -Pin 7/8
USB port	5Vdc -1A max
DC Output	9Vdc/12Vdc (selectable) 2A max
Overload capability	< 130%
Transfer time	0 ms
Battery	
Type	Lithium Polymer transportable by plane (33Wh)
Backup time (typical)	240 min
Environmental specification	
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)
Humidity	< 95% without condensation
Maximum altitude	3000 m
IP protection	IP20
Certifications	CE

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Included






230 Vac

8 outlets

TO PROTECT ALL YOUR DEVICES



1 On/Off switch 2 Power cable 3 Input thermal protection 4 Output sockets with child protection and blackout protection 5 Filtered output socket with child protection
6 5Vdc 2.1A USB Charger 7 USB Port 8 RJ11/45 Port

Main Specifications

- Personal Computer, Modem/Router, Cash Register, Pos
- Automatic Voltage Regulation circuit (AVR)
- USB Charger (5V 2.1A) port
- Easy replacement batteries
- Rear slots for wall mounting

- Output sockets with child protection for blackout protection
- Output sockets with child protection for overvoltage protection
- USB port
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.



Specifications

UPS Model	ERA PLUS STRIP 1.000	ERA PLUS STRIP 1.000
Code	FGCERAPLS1002SCH	FGCERAPLS1002UK
Max Computer Power*	1.000VA/700W	
Technology	Line Interactive with stabilizer	
Cooling	Natural	
Audible noise	< 40 dBA to 1 m	
Input connection	Fixed cable with Schuko plug	Fixed cable with UK plug
Outlets	4 UPS outputs Schuko/Italian + 4 only filtered outputs Schuko/Italian	4 UPS outputs UK + 4 only filtered outputs UK
Dimension (UPS) WxHxD	20x10x34,5 cm	26,9x14,6x42,5 cm
Dimension (with packing) WxHxD		
Weight	4,4 Kg	
Input		
Number of phases	1Ph+N	
Nominal voltage	Single-phase 230Vac	
Input voltage range	+20%/-25%	
Nominal frequency	50/60 Hz (automatic selection)	
Input frequency range	+/-5%	
Output		
Number of phases	1Ph+N	
Nominal voltage	Single-phase 230Vac	
Voltage regulation (Line mode)	AVR (Automatic Voltage Regulation)	
Voltage regulation (Battery mode)	+/-5%	
Frequency	50/60 Hz (automatic selection)	
Inverter waveform	Modified sinewave	
Overload capability	< 130%	
Transfer time	2 ms (typical)	
Battery		
Type	Lead acid, sealed, maintenance free	
Backup time (typical)	10-40 min	
Environmental specification		
Working temperature	From 0 to 40 °C (recommended from 20 to 25 °C)	
Humidity	< 95% without condensation	
Maximum altitude	3000 m	
IP protection	IP20	
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)	

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

* This UPS is designed and sized for the protection of IT workstations. The power expressed as "Max Computer Power" corresponds to the sum of the Plate Powers, of the Switching Power Supplies present in the IT Stations to be protected. For any use with devices other than IT workstations, it is advisable to seek specific advice from the manufacturer

Available on request with input/output nominal voltage 110Vac or 120Vac and with input plug and output sockets for specific country.



TECNOManager
UPS Management Software

TECNOWARE®





① On/Off button ② LCD Display ③ USB port ④ Line protection Telephone/Modem/Lan RJ11/RJ45 ⑤ Output sockets with blackout protection
⑥ Input fuse ⑦ Input socket

Main Specifications

- For Small server, Local Area Networks (LAN), Switch, HUB, Firewall, Video Surveillance Systems
- Automatic Voltage Regulation circuit (AVR)
- Output sockets with blackout protection
- USB Port
- Mounting in Rack cabinet 19"
- UPS Management TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

Specifications

UPS Model	ERA PLUS 1.200 RACK MOUNT
Code	FGCERAPL1202RSCH
Max Computer Power*	1.200VA/840W
Technology	Line Interactive with stabilizer
Cooling	Natural
Audible noise	< 40 dBA to 1 m
Dimension UPS WxHxD	43,8x8,8x23 cm (2U)
Dimension with packing WxHxD	52x19,5x40,5 cm
Weight	6,5 Kg
Input	
Number of phases	1Ph+N
Nominal voltage	Single-phase 230Vac
Input voltage range	+20%/-25%
Nominal frequency	50/60 Hz (automatic selection)
Input frequency range	+/-5%
Output	
Number of phases	1Ph+N
Nominal voltage	Single-phase 230Vac
Voltage regulation (Line mode)	AVR (Automatic Voltage Regulation)
Voltage regulation (Battery mode)	+/-5%
Frequency	50/60 Hz (automatic selection)
Inverter waveform	Modified sinewave
Overload capability	< 130%
Transfer time	2 ms (typical)
Battery	
Type	Lead acid, sealed, maintenance free
Backup time (typical)	10-40 min
Environmental specification	
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)
Humidity	< 95% without condensation
Maximum altitude	3000 m
IP protection	IP20
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

* This UPS is designed and sized for the protection of IT workstations. The power expressed as "Max Computer Power" corresponds to the sum of the Plate Powers, of the Switching Power Supplies present in the IT Stations to be protected. For any use with devices other than IT workstations, it is advisable to seek specific advice from the manufacturer

Available on request with input/output nominal voltage 110Vac or 120Vac and with input plug and output sockets for specific country.



TECNOManager
UPS Management Software

TECNOWARE®



230 Vac



① On/off switch ② LED Line/Battery/Fault ③ Power cable ④ Input socket ⑤ Input thermal protection ⑥ Output sockets with child protection and blackout protection
⑦ Output sockets with blackout protection ⑧ USB Port (only for Era Plus 1.200 and Era Plus 1.600)

Main Specifications

- Personal Computer, Modem, Local Area Networks, Video Surveillance Systems
- Automatic Voltage Regulation circuit (AVR)
- Output sockets with child protection for blackout protection
- Output sockets with child protection for overvoltage protection
- USB Port (only for Era Plus 1.200-1.600)
- UPS Management Software compatible with Windows, Mac OS X, Unix, Linux, etc.

Specifications

UPS Model	ERA PLUS 600	ERA PLUS 800	ERA PLUS 950	ERA PLUS 1.200	ERA PLUS 1.600
Schuko version code	FGCERAPL602SCH	FGCERAPL802SCH	FGCERAPL952SCH	FGCERAPL1202SCH	FGCERAPL1602SCH
IEC version code	FGCERAPL602IEC	FGCERAPL802IEC	FGCERAPL952IEC	FGCERAPL1202IEC	FGCERAPL1602IEC
Universal version code	FGCERAPL602UNI	FGCERAPL802UNI	FGCERAPL952UNI	FGCERAPL1202UNI	FGCERAPL1602UNI
Max Computer Power*	600VA/420W	800VA/560W	950VA/665W	1.200VA/840W	1.600VA/1.120W
Technology	Line Interactive with stabilizer				
Interface	-				
Cooling	Natural				
Audible noise	< 40 dB(A to 1 m				
Dimension (UPS) WxHxD	10,1x14,2x27,9 cm				
Dimension (with packing) WxHxD	18x22x34cm				
Weight	3,7 Kg	3,9 Kg	4,2 Kg	4,5 Kg	5 Kg
Input	1Ph+N				
Number of phases	Single-phase 230Vac				
Nominal voltage	+20%/-25%				
Input voltage range	50/60 Hz (automatic selection)				
Nominal frequency	+/-5%				
Input frequency range					
Output	1Ph+N				
Number of phases	Single-phase 230Vac				
Nominal voltage	AVR (Automatic Voltage Regulation)				
Voltage regulation (Line mode)	+/-5%				
Voltage regulation (Battery mode)	50/60 Hz (automatic selection)				
Frequency	Modified sinewave				
Inverter waveform	< 130%				
Overload capability	2 ms (typical)				
Transfer time					
Battery	Lead acid, sealed, maintenance free				
Type	10-40 min				
Backup time (typical)					
Environmental specification	From 0 to 55 °C (recommended from 20 to 25° C)				
Working temperature	< 95% without condensation				
Humidity	3000 m				
Maximum altitude	IP20				
IP protection	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)				

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

* This UPS is designed and sized for the protection of IT workstations. The power expressed as "Max Computer Power" corresponds to the sum of the Plate Powers, of the Switching Power Supplies present in the IT Stations to be protected. For any use with devices other than IT workstations, it is advisable to seek specific advice from the manufacturer



① On/off switch ② Power cable ③ Input thermal protection ④ Output sockets with child protection and blackout protection ⑤ Filtered output socket with child protection
⑥ USB Port (only for Era Plus 1.200 and Era Plus 1.600)

Main Specifications


- Personal Computer, Modem, Local Area Networks, Video Surveillance Systems
- Automatic Voltage Regulation circuit (AVR)
- Output sockets with child protection for blackout protection
- Output sockets with child protection for overvoltage protection
- USB Port (only for Era Plus 1.200 and Era Plus 1.600)
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

Specifications

UPS Model	ERA PLUS 600	ERA PLUS 800	ERA PLUS 950	ERA PLUS 1.200	ERA PLUS 1.600
Code	FGCERAPL602NEM	FGCERAPL802NEM	FGCERAPL950NEM	FGCERAPL1202NEM	FGCERAPL1602NEM
Max Computer Power*	600VA/420W	800VA/560W	950VA/665W	1.200 VA/840W	1.600VA/1.120W
Technology	Line Interactive with stabilizer				
Interface	-			USB Port	
Cooling			Natural		
Audible noise			< 40 dBa at 1 m		
Dimension (UPS) WxHxD			10,1x14,2x27,9 cm		
Dimension (with packing) WxHxD			18x22x34cm		
Weight	3,7 Kg	3,9 Kg	4,2 Kg	4,5 Kg	5 Kg
Input					
Number of phases			1Ph+N		
Nominal voltage			Single-phase 120Vac		
Input voltage range			+25%/-30%		
Nominal frequency			50/60 Hz (automatic selection)		
Input frequency range			+/-5Hz		
Output					
Number of phases			1Ph+N		
Nominal voltage			Single-phase 120Vac		
Voltage regulation (Line mode)			AVR (Automatic Voltage Regulation)		
Voltage regulation (Battery mode)			+/-5%		
Frequency			50/60 Hz (automatic selection)		
Inverter waveform			Modified sinewave		
Overload capability			< 130%		
Transfer time			2 ms (typical)		
Battery					
Type			Lead acid, sealed, maintenance free		
Backup time (typical)			10-40 min		
Environmental specification					
Working temperature			From 0 to 55 °C (recommended from 20 to 25° C)		
Humidity			< 95% without condensation		
Maximum altitude			3000 m		
IP protection			IP20		

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

* This UPS is designed and sized for the protection of IT workstations. The power expressed as "Max Computer Power" corresponds to the sum of the Plate Powers, of the Switching Power Supplies present in the IT Stations to be protected. For any use with devices other than IT workstations, it is advisable to seek specific advice from the manufacturer



230 Vac

① On/off switch ② LED Line/Battery/Fault ③ Power cable ④ Input socket ⑤ Input thermal protection ⑥ Output sockets with blackout protection ⑦ Output sockets with child protection and blackout protection ⑧ Filtered output socket ⑨ Filtered output socket with child protection ⑩ Telephone line/Modem/Lan RJ11/RJ45 protection ⑪ USB Port

Main Specifications

- Personal Computer, Modem, Local Area Networks, Video Surveillance Systems
- Automatic Voltage Regulation circuit (AVR)
- Output sockets with child protection for blackout protection
- Output sockets with child protection for overvoltage protection
- USB Port
- Telephone line/Modem/Lan RJ11/RJ45 protection
- UPS Management Software compatible with Windows, Mac OS X, Unix, Linux, etc.

Specifications

UPS Model	ERA PLUS 2.100	ERA PLUS 2.600
IEC version code	FGCERAPL2102IEC	FGCERAPL2602IEC
Universal version code	FGCERAPL2102UNI	FGCERAPL2602UNI
Max Computer Power*	2.100VA/1.470W	2.600VA/1.820W
Technology	Line Interactive with stabilizer	
Interface	USB Port + RJ11/RJ45 Filter	
Cooling	Natural	Fan cooling
Audible noise	< 40 dBA to 1 m	< 45 dBA to 1 m
Dimension (UPS) WxHxD		13x18,2x32 cm
Dimension (with packing) WxHxD		23,2x27,3x39 cm
Weight	8,6 Kg	10,4 Kg
Input		
Number of phases	1Ph+N	
Nominal voltage	Single-phase 230Vac	
Input voltage range	+20%/-25%	
Nominal frequency	50/60 Hz (automatic selection)	
Input frequency range	+/-5%	
Output		
Number of phases	1Ph+N	
Nominal voltage	Single-phase 230Vac	
Voltage regulation (Line mode)	AVR (Automatic Voltage Regulation)	
Voltage regulation (Battery mode)	+/-5%	
Frequency	50/60 Hz (automatic selection)	
Inverter waveform	Modified sinewave	
Overload capability	< 130%	
Transfer time	2 ms (typical)	
Battery		
Type	Lead acid, sealed, maintenance free	
Backup time (typical)	10-90 min	
Environmental specification		
Working temperature	From 0 to 55 °C (recommended from 20 to 25° C)	
Humidity	< 95% without condensation	
Maximum altitude	3000 m	
IP protection	IP20	
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)	

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

* This UPS is designed and sized for the protection of IT workstations. The power expressed as "Max Computer Power" corresponds to the sum of the Plate Powers, of the Switching Power Supplies present in the IT Stations to be protected. For any use with devices other than IT workstations, it is advisable to seek specific advice from the manufacturer



① On/off switch ② Power cable ③ Input thermal protection ④ Output sockets with child protection and blackout protection ⑤ Filtered output socket with child protection
 ⑥ Telephone line/Modem/Lan RJ11/RJ45 protection ⑦ USB Port

Main Specifications

- Personal Computer, Modem, Local Area Networks, Video Surveillance Systems
- Automatic Voltage Regulation circuit (AVR)
- Output sockets with child protection for blackout protection
- Output sockets with child protection for overvoltage protection
- USB Port
- Telephone line/Modem/Lan RJ11/RJ45 protection
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

Specifications

UPS Model	ERA PLUS 2.100	ERA PLUS 2.600
Code	FGCERAPL2102NEM	FGCERAPL2602NEM
Max Computer Power*	2.100VA/1.470W	2.600VA/1.820W
Technology	Line Interactive with stabilizer	
Interface	USB Port + RJ11/RJ45 Filter	
Cooling	Natural	Fan cooling
Audible noise	< 40 dBA a 1 m	< 45 dBA a 1 m
Dimension (UPS) WxHxD	13x18,2x32 cm	
Dimension (with packing) WxHxD	23,2x27,3x39 cm	
Weight	8,6 Kg	10,4 Kg
Input		
Number of phases	1Ph+N	
Nominal voltage	Single-phase 120Vac	
Input voltage range	+25%/-30%	
Nominal frequency	50/60 Hz (automatic selection)	
Input frequency range	+/-5Hz	
Output		
Number of phases	1Ph+N	
Nominal voltage	Single-phase 120Vac	
Voltage regulation (Line mode)	AVR (Automatic Voltage Regulation)	
Voltage regulation (Battery mode)	+/-5%	
Frequency	50/60 Hz (automatic selection)	
Inverter waveform	Modified sinewave	
Overload capability	< 130%	
Transfer time	2 ms (typical)	
Battery		
Type	Lead acid, sealed, maintenance free	
Backup time (typical)	10-90 min	
Environmental specification		
Working temperature	From 0 to 55 °C (recommended from 20 to 25° C)	
Humidity	< 95% without condensation	
Maximum altitude	3000 m	
IP protection	IP20	

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

* This UPS is designed and sized for the protection of IT workstations. The power expressed as "Max Computer Power" corresponds to the sum of the Plate Powers, of the Switching Power Supplies present in the IT Stations to be protected. For any use with devices other than IT workstations, it is advisable to seek specific advice from the manufacturer



DESIGNED
FOR
**ACTIVE
PFC**

① On/Off button ② LED Line/Battery/Fault ③ Power cable ④ Protezione termica d'ingresso ⑤ Output sockets with blackout protection

⑥ USB Port

Main Specifications

- For Personal Computer, Console Game, Local Area Networks (LAN), Video Surveillance Systems
- Designed for Power Supplies with active PFC
- Automatic Voltage Regulation circuit (AVR)
- Output sockets with child protection for blackout protection
- Output sockets with child protection for overvoltage protection
- USB port
- UPS Management Software compatible with Windows, Mac OS X, Unix, Linux, etc.

Specifications

UPS Model	ERA PLUS ACTIVE 1.200	ERA PLUS ACTIVE 1.600
Code	FGCERAPLAT1202SCH	FGCERAPLAT1602SCH
Max Computer Power*	1.200VA/840W	1.600VA/1.120W
Technology	Line Interactive with stabilizer compatible with Active PFC	
Interface	USB port	
Cooling	Natural	
Audible noise	< 40 dBA at 1 m	
Dimension (UPS) WxHxD	20,7x8,2x22,8cm	
Dimension (with packing) WxHxD	28x12x28,8cm	
Weight	2,7 Kg	3,1 Kg
Input		
Number of phases	1Ph+N	
Nominal voltage	Single-phase 230Vac	
Input voltage range	+20%/-25%	
Nominal frequency	50/60 Hz (automatic selection)	
Input frequency range	+/-5%	
Output		
Number of phases	1Ph+N	
Nominal voltage	Single-phase 230Vac	
Voltage regulation (Line mode)	AVR (Automatic Voltage Regulation)	
Voltage regulation (Battery mode)	+/-5%	
Frequency	50/60 Hz (automatic selection)	
Inverter waveform	Modified sinewave	
Overload capability	< 130%	
Transfer time	2 ms (typical)	
Battery		
Type	Lead acid, sealed, maintenance free	
Backup time (typical)	10-40 min	
Environmental specification		
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)	
Humidity	< 95% without condensation	
Maximum altitude	3000 m	
IP protection	IP20	
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)	

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

* This UPS is designed and sized for the protection of IT workstations. The power expressed as "Max Computer Power" corresponds to the sum of the Plate Powers, of the Switching Power Supplies present in the IT Stations to be protected. For any use with devices other than IT workstations, it is advisable to seek specific advice from the manufacturer

Available on request with input/output nominal voltage 110Vac or 120Vac and with input plug and output sockets for specific country.



1 Display LCD 2 On/Off button - Control buttons 3 5V 2.1A USB Charger 4 Output socket with blackout protection 5 Filtered output socket 6 Input socket
7 Input fuse 8 Line protection Telephone/Modem/Lan RJ11/RJ45 9 USB port

Main Specifications

- For Workstation, PC Game, Console Game, Personal Computer, Server, Local Area Networks (LAN), Home Theatre, TV, HI-FI, Fireplace heating systems (excluding Exa PLUS 1.100), Home heating system
- Silent (the fan works only in Battery Mode or boost/buck AVR mode)
- Display with Intelligent Backlighting System
- 2 USB Charger Ports (5V 2.1A)
- Automatic Voltage Regulation circuit (AVR)
- Sinewave output
- Hot Swap battery
- Output sockets with blackout protection
- Output sockets for surge protection
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

Specifications

UPS Model	EXA PLUS 1.100	EXA PLUS 1.600	EXA PLUS 2.100
Code	FGCEXAPL1102IEC	FGCEXAPL1602IEC	FGCEXAPL2102IEC
Max Computer Power*	1.100VA /770W	1.600VA/1.120W	2.100VA/1.470W
Technology	Line Interactive with stabilizer		
LCD Display	UPS status, input/output voltage, input/output frequency, load level, battery capacity, warning or fault error code. (the display backlighting is normally off, switch on only after a key is pressed)		
Cooling	Fan cooling (only in battery mode, charging mode or boost/buck AVR mode)		
Audible noise	< 12 dBA 1m (line mode) < 40 dBA 1m (when the fan is working)	< 12 dBA 1m (line mode) < 45 dBA 1m (when the fan is working)	
Dimension (UPS) WxHxD	9,9x28x28,8 cm	9,9x28x41 cm	
Dimension (with packing) WxHxD	18x37,6x37,3 cm	18x37,6x49,5 cm	
Weight	7,4 Kg	11,8 Kg	13,1Kg
Input			
Number of phases		1Ph+N	
Nominal voltage		Single-phase 230Vac	
Input voltage range		+20%/-25%	
Nominal frequency		50/60 Hz (automatic selection)	
Input frequency range		+/-5%	
Output			
Number of phases		1Ph+N	
Nominal voltage		Single-phase 230Vac	
Voltage regulation (Line mode)		AVR (Automatic Voltage Regulation)	
Voltage regulation (Battery mode)		+/-5%	
Frequency		50/60 Hz (automatic selection)	
Inverter waveform		Sinewave	
Overload capability		< 130%	
Transfer time		2 ms (typical)	
Battery			
Type		Lead acid, sealed, maintenance free	
Backup time (typical)		10-30 min	
Environmental specification			
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)		
Humidity	< 95% without condensation		
Maximum altitude	3000 m		
IP protection	IP20		
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)		

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

* This UPS is designed and sized for the protection of IT workstations. The power expressed as "Max Computer Power" corresponds to the sum of the Plate Powers, of the Switching Power Supplies present in the IT Stations to be protected. For any use with devices other than IT workstations, it is advisable to seek specific advice from the manufacturer

Available on request with input/output nominal voltage 110Vac or 120Vac and with input plug and output sockets for specific country.



TECNOManager

TECNOWARE®





1 Input socket 2 Input Thermal protection 3 IEC320 C13 output sockets with Blackout protection 4 IEC320 C19 output socket with Blackout protection
5 USB port 6 RS232 port 7 Slot for SNMP, Dry Contact or MODBUS interface 8 EPO connector 9 Connector for additional Battery Box

Main Specifications

For Workstation, PC Game, Personal Computer, Server, Local Area Networks (LAN)

- Designed for silent environment (the fan works only in Battery Mode or boost/buck AVR mode)
- Display with Intelligent Backlighting System
- Automatic Voltage Regulation circuit (AVR)
- Intelligent slot for SNMP or Dry Contact card or MODBUS
- Sinewave output
- Battery charging system controlled by microprocessor
- Output sockets with blackout and surge protection
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

Specifications

UPS Model	EXA PLUS 3.000	EXA PLUS 4.500
Code	FGCEXAPL3002IEC	FGCEXAPL4502IEC
Max Computer Power*	3.000VA/2.100W	4.500VA/3.150W
Technology	Line Interactive with stabilizer	
LCD Display	UPS status, input/output voltage, input/output frequency, load level, battery capacity, warning or fault error code. (the display backlighting is normally off, switch on only after a key is pressed)	
Cooling	Fan cooling (only in battery mode, charging mode or boost/buck AVR mode)	
Audible noise	< 45 dBA to 1 m	
Dimension UPS LxHxP	14,5x22x45,5 cm	19x31,8x42,1 cm
Dimension (with packing) LxHxP	23x32,5x54 cm	32x46x56 cm
Weight	19,7 Kg	29 Kg
Input		
Number of phases	1Ph+N	
Nominal voltage	208Vac/220Vac/230Vac/240Vac	
Input voltage range	162-290Vac	
Nominal frequency	50/60 Hz (selectable)	
Output		
Number of phases	1F+N	
Nominal voltage	208Vac/220Vac/230Vac/240Vac (selectable)	
Static voltage Regulation at %100 linear load (On-Line and battery mode)	±1,5%	
Voltage THD at rated linear load	<2% (linear load), <5% (non-linear load)	
Crest factor	3:1	
Frequency	50/60 Hz (selectable)	
Inverter waveform	Sinewave	
Overload capability	< 130%	
Transfer time	2 ms (typical)	
Battery		
Type	Lead acid, sealed, maintenance free	
Backup time (typical)	10-30 min	
Extended autonomy	-	External Battery Box (optional)
Environmental specification		
Working temperature	From 0 to 40 °C (recommended from 20 to 25 °C)	
Humidity	< 95% without condensation	
Maximum altitude	3000 m	
IP protection	IP20	
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)	

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

* This UPS is designed and sized for the protection of IT workstations. The power expressed as "Max Computer Power" corresponds to the sum of the Plate Powers, of the Switching Power Supplies present in the IT Stations to be protected. For any use with devices other than IT workstations, it is advisable to seek specific advice from the manufacturer

Accessories

Model	Code
Bypass Box for UPS RT from 3 KVA to 4.5 KVA	FGCBYPIEC
Dry Contact DB9 Interface	FGCEVODSDRY3
Dry Contact 9 PIN Interface	FGCEVODSDRY4

Model	Code
SNMP Internal Interface	FGCNETAG7
ModBus RS485 Interface	FGCMODBUS



① Connector for the UPS Battery Box connection ② Extra Battery Box connector ③ Power socket for the battery charger circuit
 ④ Thermal Fuse protecting the battery charger circuit ⑤ Thermal switch for battery circuit


Main Specifications

- Internal battery charger on every unit
- Units can be expanded infinitely
- Batteries with thermal circuit protection
- Easy connection to UPS
- Convertible format (Tower or Rack 19")

Specifications

Model	BATTERY BOX FOR EXA PLUS 4.500	
Code	FBBEDP3602RT/09	FBBEDP3602RT/18
Positioning	Into Tower or 19" Rack cabinet (2U) positioning	
Dimension (Box) WxHxD	43,8x8,8x63 cm	
Dimension (with packing) WxHxD	60x24x75 cm	
Weight	30 Kg	43 Kg
Battery	Lead acid, sealed, maintenance free	
Type	Internal Battery Charger	
Nominal input voltage	230Vac	
Nominal input frequency	50/60Hz	
Nominal charging voltage	82,2Vdc	
Max charging current	1A	
Protection	Thermal fuse Magnetothermic switch	
Battery charge input		
Battery circuit		
Environmental specification	From 0 to 55 °C (recommended from 20 to 25 °C) < 95% without condensation	
Working temperature		
Humidity		
Maximum altitude	3000 m	
IP protection	IP20	
Certifications	CE	

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.



1 Input connection 2 Input Thermal protection 3 IEC320 C13 output sockets with Blackout protection
 4 Output Terminal block with Blackout protection (for EVO DSP Plus 5.5 PF 0,9 to replace USB e RS232) 5 USB port 6 RS232 port 7 Slot for SNMP, Dry Contact or MODBUS interface
 8 EPO connector 9 Connector for additional Battery Box
 10 Switch mains input 11 Input/output terminal block

POWER FACTOR

0,9

HIGH EFFICIENCY
94%

Main Specifications

- For Local Area Network (LAN), Data Centers, Industrial equipment, Electromedical equipment
- Power Factor 0,9
- Rectifier realized by IGBT technology

- Compatible with Generators
- Battery charging system controlled by micro processor
- Intelligent slot for SNMP or Dry Contact card or MODBUS

- Static Bypass
- High efficiency and low operating cost
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

Specifications

UPS Model	EVO DSP PLUS 1.200 PF 0,9	EVO DSP PLUS 2.400 PF 0,9	EVO DSP PLUS 3.600 PF 0,9	EVO DSP PLUS 5.500 PF 0,9
Code	FGCEDP1202IEC	FGCEDP2402IEC	FGCEDP3602IEC	FGCEDP5502MM
Nominal Power	1.200 VA	2.400 VA	3.600 VA	5.5 kVA
Active Power	1.080 W	2.160 W	3.240 W	4.950 W
Power factor			0,9	
Technology	On-Line Double Conversion transformerless (VFI-SS-111)			
Cooling	Cooling fan			
Audible noise	< 45 dBA to 1 m			
Dimension UPS LxHxP	14,5x22x28,2 cm	14,5x22x39,7 cm	19x31,8x42,1 cm	< 48 dBA a 1 m
Dimension (with packing) LxHxP	23x33x37 cm	23x33x48 cm	33x46x56 cm	19x57,3x36,9 cm
Weight	10 Kg	17 Kg	27 Kg	33x83,5x50,5 cm
Input				46 Kg
Number of phases	1Ph+N			
Nominal voltage	208Vac/220Vac/230Vac/240Vac			
Input voltage range	110-300Vac			
Nominal frequency	50/60 Hz (selectable)			
Input frequency range (On-Line mode)	+/- 7%			
Input power factor	0,99			
Output				
Number of phases	1Ph+N			
Nominal voltage	208Vac/220Vac/230Vac/240Vac (selectable)			
Static voltage Regulation at %100 linear load (On-Line and battery mode)	±1%			
Voltage THD at rated linear load	<2% (linear load) <8% (non-linear load)			
Crest factor	5:1			
Frequency	50/60 Hz (selectable)			
Free running frequency	±0,2 Hz			
Inverter waveform	Sinewave			
Overload capability (on-line mode)	110% only audible warning, 110-130% for 30 s, >130% for 100 ms			
Overload capability (battery mode)	110% only audible warning, 110-130% for 30 s, >130% for 100 ms			
Efficiency	94%, calculated in double conversion metod 100% load according to standard 62040-3			
Transfer time	0 ms (On-Line)			
Battery				
Type	Lead acid, sealed, maintenance free			
Extended autonomy	External Battery Box (optional)			
Environmental specification				
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)			
Humidity	< 95% without condensation			
Maximum altitude	3000 m			
IP protection	IP20			
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)			

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Accessories

Model	Code
Bypass Box for UPS from 1.2 KVA to 3.6 KVA	FGCBYPIEC
Bypass Box for UPS from 5.5 KVA	FGCBYP10MM2
Dry Contact DB9 Interface	FGCEVODSDRY3

Model	Code
Dry Contact 9 PIN Interface	FGCEVODSDRY4
SNMP Internal Interface	FGCNETAG7
ModBus RS485 Interface	FGCMODBUS



① Connector for the UPS Battery Box connection ② Extra Battery Box connector ③ Power socket for the battery charger circuit
 ④ Thermal Fuse protecting the battery charger circuit ⑤ Thermal switch for battery circuit

Main Specifications

- Internal battery charger on every unit
- Units can be expanded infinitely
- Batteries with thermal circuit protection
- Easy connection to UPS
- Convertible format (Tower or Rack 19")

Specifications

Model	BATTERY BOX FOR EVO DSP PLUS 3.600	
Code	FBBEDP3602RT/09	FBBEDP3602RT/18
Positioning	Into Tower or 19" Rack cabinet (2U) positioning	
Dimension (Box) WxHxD	43,8x8,8x63 cm	
Dimension (with packing) WxHxD	60x24x75 cm	
Weight	30 Kg	43 Kg
Battery	Lead acid, sealed, maintenance free	
Type	Internal Battery Charger	
Nominal input voltage	230Vac	
Nominal input frequency	50/60Hz	
Nominal charging voltage	82,2Vdc	
Max charging current	1A	
Protection	Thermal fuse Magnetothermic switch	
Battery charge input		
Battery circuit		
Environmental specification	From 0 to 55 °C (recommended from 20 to 25 °C) < 95% without condensation	
Working temperature		
Humidity		
Maximum altitude	3000 m	
IP protection	IP20	
Certifications	CE	

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

POWER
FACTOR

0,9



Ups Evo DSP PLUS 1.200 Rack Tower PF 0,9



Ups Evo DSP MM 2.400 Rack Tower PF 0,9



Ups Evo DSP MM 3.600 Rack Tower PF 0,9

① Input socket ② Input Thermal protection ③ IEC320 C13 output sockets with Blackout protection ④ IEC320 C19 output socket with Blackout protection
 ⑤ USB port ⑥ RS232 port ⑦ Slot for SNMP, Dry Contact or MODBUS interface ⑧ EPO connector ⑨ Connector for additional Battery Box

Main Specifications

- For Local Area Network (LAN), Data Centers, Industrial equipment, Electromedical equipment
- Convertible format (Tower or Rack 19") with adjustable display
- Power Factor 0,9
- Rectifier realized by IGBT technology
- Compatible with Generators
- Battery charging system controlled by microprocessor
- Hot Swap Battery
- Static Bypass
- Intelligent slot for SNMP or Dry Contact card or MODBUS
- High efficiency and low operating cost
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

**HIGH
EFFICIENCY
94%**

Specifications

UPS Model	EVO DSP PLUS 1.200 RACK TOWER PF 0,9	EVO DSP PLUS 2.400 RACK TOWER PF 0,9	EVO DSP PLUS 3.600 RACK TOWER PF 0,9
Code	FGCEDP1202RTIEC	FGCEDP2402RTIEC	FGCEDP3602RTIEC
Nominal Power	1.200 VA	2.400 VA	3.600 VA
Active power	1.080 W	2.160 W	3.240 W
Power factor	0,9		
Technology	On-Line Double Conversion transformerless (VFI-SS-111)		
Cooling	Fan cooling		
Audible noise	< 45 dBA to 1 m		
Positioning	Tower positioning or Into 19" rack (2U)		
Dimension UPS LxHxP	43,8x8,8x31 cm	43,8x8,8x41 cm	43,8x8,8x63 cm
Dimension (with packing) LxHxP	50x18x40 cm	56x18x50 cm	76x20x60 cm
Weight	12 Kg	19 Kg	29 Kg
Input			
Number of phases	1Ph+N		
Nominal voltage	208Vac/220Vac/230Vac/240Vac		
Input voltage range	110-300Vac		
Nominal frequency	50/60 Hz (selectable)		
Input frequency range (On-Line mode)	+/- 7%		
Input power factor	0,99		
Output			
Number of phases	1Ph+N		
Nominal voltage	208Vac/220Vac/230Vac/240Vac (selectable)		
Static voltage Regulation at %100 linear load (On-Line and battery mode)	$\pm 1\%$		
Voltage THD at rated linear load	<2% (linear load), <8% (non-linear load)		
Crest factor	3:1		
Frequency	50/60 Hz (selectable)		
Free running frequency	$\pm 0,2$ Hz		
Inverter waveform	Sinewave		
Overload capability	110% only audible warning, 110-130% for 30 sec, >130% for 100 ms		
Efficiency	94%, calculated in double conversion metod 100% load according to standard 62040-3		
Transfer time	0 ms (On-Line)		
Battery			
Type	Lead acid, sealed, maintenance free		
Backup time (Typical)	10-30 min		
Extended autonomy	-		External Battery Box (optional)
Environmental specification			
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)		
Humidity	< 95% without condensation		
Maximum altitude	3000 m		
IP protection	IP20		
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)		

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Accessories

Model	Code
Bypass Box for UPS RT from 1.2 KVA to 3.6 KVA	FGCBYPIEC
Dry Contact DB9 Interface	FGCEVODSDRY3
Dry Contact 9 PIN Interface	FGCEVODSDRY4

Model	Code
SNMP Internal Interface	FGCNETAG7
ModBus RS485 Interface	FGCMODBUS
Kit 2 shelves for UPS Rack Installation	FGCKITEVORT



TECNOManager

TECNOWARE
UPS Management Software





① Connector for the UPS Battery Box connection ② Extra Battery Box connector ③ Power socket for the battery charger circuit
 ④ Thermal Fuse protecting the battery charger circuit ⑤ Thermal switch for battery circuit


Main Specifications

- Internal battery charger on every unit
- Units can be expanded infinitely
- Batteries with thermal circuit protection
- Easy connection to UPS
- Convertible format (Tower or Rack 19")

Specifications

Model	BATTERY BOX FOR EVO DSP PLUS 3.600 RACK TOWER PF 0,9	
Code	FBBEDP3602RT/09	FBBEDP3602RT/18
Positioning	Into Tower or 19" Rack cabinet (2U) positioning	
Dimension (Box) WxHxD	43,8x8,8x63 cm	
Dimension (with packing) WxHxD	60x24x75 cm	
Weight	30 Kg	43 Kg
Battery	Lead acid, sealed, maintenance free	
Internal Battery Charger		
Nominal input voltage	230Vac	
Nominal input frequency	50/60Hz	
Nominal charging voltage	82,2Vdc	
Max charging current	1A	
Protection		
Battery charge input	Thermal fuse	
Battery circuit	Magnetothermic switch	
Environmental specification		
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)	
Humidity	< 95% without condensation	
Maximum altitude	3000 m	
IP protection	IP20	
Certifications	CE	

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.



Ups Evo DSP Plus 6.0-10.0 PF 1

① RS232 port ② USB port ③ Slot for SNMP interface, Dry Contact or MODBUS ④ EPO connector ⑤ Switch mains input ⑥ Input/output terminal block
 ⑦ Connector for external Battery Box ⑧ Manual bypass switch for maintenance ⑨ Interface for parallel connection

Main Specifications

- Local Area Network (LAN), Data Centers, Industrial equipment, Electromedical equipment
- Power factor 1
- Rectifier realized by IGBT technology
- Compatible with generators
- Battery charging system controlled by microprocessor
- Extension Back-up time by external Battery box
- Static and Manual Bypass
- Expandable up to 2 units in parallel
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

HIGH
EFFICIENCY
94%

Specifications

Modello UPS	EVO DSP PLUS 6.0 PF 1				EVO DSP PLUS 10.0 PF 1			
Codice	FGCEDP6MM2/00	FGCEDP6MM2/C	FGCEDP6MM2/D	FGCEDP6MM2/E	FGCEDP10MM2/00	FGCEDP10MM2/C	FGCEDP10MM2/D	FGCEDP10MM2/E
Nominal power			6 KVA				10 KVA	
Active power			6 KW				10 KW	
Power factor					1			
Technology	On-Line Double Conversion transformerless (VFI-SS-111)							
Cooling	Fan cooling							
Audible noise	< 55 dBA to 1 m				< 58 dBA to 1 m			
Dimension (UPS) WxHxD	19x68,8x36,9 cm				19x68,8x44,2 cm			
Dimension (with packing) WxHxD	32x92,2x51,4 cm				32x92,2x58,7 cm			
Weight	18 Kg	57 Kg	62 Kg	65 Kg	23 Kg	62 Kg	67 Kg	70 Kg
Input								
Number of phases	1Ph+N							
Nominal voltage	208Vac/220Vac/230Vac/240Vac							
Input voltage range	176Vac-300Vac from 50% to the 100% of loading, 110Vac-300Vac up to 50% load							
Nominal frequency	50/60 Hz (selectable)							
Input frequency range (On-Line mode)	±7%							
Input power factor	0,99							
Output								
Number of phases	1Ph+N							
Nominal voltage	208Vac/220Vac/230Vac/240Vac							
Voltage Regulation at %100 linear load (On-Line and Battery mode)	±2%							
Voltage THD at rated linear load	<3% (linear load), <5% (non-linear load)							
Crest factor	3:1							
Frequency	50/60 Hz (selectable)							
Frequency stability	±0,1 Hz							
Inverter waveform	Sinewave							
Overload capability (Line mode)	110% for 30 minutes, 130% for 5 minutes, >130% for 10 seconds							
Overload capability (Battery mode)	110% for 3 minutes, 130% for 30 seconds, >130% for 10 seconds							
Efficiency	94%, calculated in double conversion mode at 100% load to 100% load according to standard 62040-3							
Transfer time	0 ms (On-Line)							
Battery								
Type	Lead acid, sealed, maintenance free							
Installed inside	-	16 elements				16 elements		
Extended autonomy					External Battery Box (optional)			
Environmental specification								
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)							
Humidity	< 95% without condensation							
Maximum altitude	3000 m							
IP protection	IP20							
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)							

Accessories

Model	Code
Bypass Box for Evo Dsp Plus 6.0 and 10.0	FGCBYP10MM2
Dry Contact DB9 Interface	FGCEVODSDRY3
Dry Contact 9 PIN Interface	FGCEVODSDRY4

Model	Code
SNMP for Evo Dsp Plus MM	FGCNETAG7
ModBus RS485 Interface	FGCMODBUS

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.



TECNOManager
UPS Management Software

TECNOWARE®





① Thermal Fuse protecting the battery charger circuit ② Power Socket for the battery charger circuit ③ Thermal switch for battery circuit
 ④ Connector for the UPS connection ⑤ Extra Battery Box connector


Main Specifications

- Internal battery charger on every unit
- Units can be expanded infinitely
- Batteries with thermal circuit protection
- Easy connection to UPS
- Reduced dimensions
- Easy installation and maintenance

Specifications

Model	BATTERY BOX FOR EVO DSP PLUS 6.0-10.0 PF 1												
Code	FBBEVDP192A/00 FBBEVD192A/07 FBBEVD192A/14 FBBEVD192A/21 FBBEVD192A/28 FBBEVD192A/09 FBBEVD192A/18 FBBEVD192A/27 FBBEVD192A/36 FBBEVD192A/11 FBBEVD192A/22 FBBEVD192A/33 FBBEVD192A/44												
Box dimension WxHxD	25 x 83,3 x 80 cm												
Pack dimension WxHxD	38 x 105,8 x 96,5 cm												
Weight	49 Kg	81,4 Kg	107,8 Kg	134,2 Kg	160,6 kg	90,5 kg	126 kg	161,5 Kg	197,1 Kg	98,2 Kg	141,4 Kg	184,6 Kg	227,8 Kg
Battery	Lead acid, sealed, maintenance free												
Type													
Internal battery charger													
Nominal input voltage	230Vac												
Nominal input frequency	50/60Hz												
Nominal charging voltage	219,2Vdc												
Max charging current	Selectable	0,7A	1,4A	2,1A	2,8A	0,9A	1,8A	2,7A	3,6A	1,1A	2,2A	3,3A	4,4A
Protection													
Battery charge input	Thermal fuse												
Battery circuit	Magnetothermic switch												
Environmental specification													
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)												
Humidity	< 95% without condensation												
Maximum altitude	3000 m												
IP protection	IP20												
Certifications	CE												

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.



UPS EVO DSP PLUS RM 6.0-10.0 PF 1

① LCD display ② LED status light ③ Multifunction buttons ④ USB port ⑤ RS232 port ⑥ EPO connector ⑦ Slot for SNMP, Dry Contact or MODBUS
 ⑧ Input/output Terminal Box ⑨ Input network switch ⑩ Battery Box connector ⑪ Interface for parallel connection

Main Specifications

- For Local Area Network (LAN), Data Centers
- Power factor 1
- Rectifier realized by IGBT technology
- Compatible with Generators
- Battery charging system controlled by microprocessor
- Static Bypass
- Expandable up to 2 units in parallel
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

HIGH
EFFICIENCY
94%

Specifications

UPS Model	EVO DSP PLUS 6.0 RACK MOUNT PF 1	EVO DSP PLUS 10.0 RACK MOUNT PF 1
Code	FGCEDP6MM2RM/00	FGCEDP10MM2RM/00
Nominal power	6 KVA	10 KVA
Active power	6 KW	10 KW
Power factor	1	
Technology	On-Line Double Conversion transformerless (VFI-SS-111)	
Cooling	Fan cooling	
Audible noise	< 48 dBA to 1 m	
Dimension (UPS) WxHxD	43.8x8.8x51.5 (2U)	
Dimension (with packing) WxHxD	59x22x71 cm	
Weight	11 Kg	13 Kg
Equipped with	1 serial cable, Tecnomanager software and 2 metal handle for 19" Rack cabinet mounting	
Input		
Number of phases	1Ph+N	
Nominal voltage	208Vac/220Vac/230Vac/240Vac	
Input voltage range	176Vac-300Vac from 50% to 100% load, 110Vac-300Vac from to 50% load	
Nominal frequency	50/60 Hz (selectable)	
Input frequency range On-Line mode	±7%	
Input power factor	0,99	
Output		
Number of phases	1Ph+N	
Nominal voltage	208Vac/220Vac/230Vac/240Vac	
Voltage Regulation at %100 linear load (On-Line and Battery mode)	±1%	
Voltage THD	<3% (linear load), <6% (non-linear load)	
Crest factor	3:1	
Frequency	50/60 Hz (selectable)	
Frequency stability	±0,1 Hz	
Inverter waveform	Sinewave	
Overload capability (Line mode)	110% for 10 minutes, 130% for 1 minute, >130% for 1 second	
Overload capability (Battery mode)	110% for 30 seconds, 130% for 10 seconds, >130% for 1 second	
Efficiency	94%, calculated in double conversion mode at 100% load to 100% load according to standard 62040-3	
Transfer time	0 ms (On-Line)	
Output connections	Terminal block	
Battery (fitted inside the external Battery Box)		
Batteries number	16 (inside the external Battery Box, for UPS operation)	
Battery charge time (typical)	6-8 hours	
Extended autonomy	External Battery Box (optional)	
Environmental specification		
Working temperature	Da 0 a 55 °C (recommended from 20 to 25 °C)	
Humidity	< 95% without condensation	
Maximum altitude	3000 m	
IP protection	IP20	
Certifications	CE (standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)	

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Accessories

Model	Code
Bypass Box for Evo Dsp Plus Rack Mount 6.0 and 10.0	FGCBYP10MMRM
Dry Contact DB9 Interface	FGCEVODSDRY3
Dry Contact 9 PIN Interface	FGCEVODSDRY4
SNMP for Ups Evo Dsp Plus	FGCNETAG7
ModBus RS485 Interface	FGCMODBUS
Kit 2 shelves for UPS Rack Installation	FGCKITEVORT



TECNOManager
UPS Management Software

 **TECNOWARE**®





1 Thermal protection for battery charger circuit 2 Power socket for the battery charger circuit 3 Thermal switch for battery circuit
4 Connector for the UPS connection 5 Extra Battery Box connector

Main Specifications

- Internal battery charger on every unit
- Units can be expanded infinitely
- Batteries with thermal circuit protection
- Easy connection to UPS
- Hot Swap batteries
- Rack format 19", height 3U
- Packaging containing separate Battery Box and Battery Pack

Specifications

Model	BATTERY BOX FOR EVO DSP PLUS 6.0-10.0 RACK MOUNT PF 1			
Code	FBBEVDR192/00	FBBEVDR192/07	FBBEVDR192/09	FBBEVDR192/11
Box dimension WxHxD		43,8 x 13,3 x 66,8 cm (3U)		
Pack dimension WxHxD		59 x 26 x 87,5 cm		
Weight	10 Kg	49 Kg	53 Kg	56 Kg
Battery				
Type		Lead acid, sealed, maintenance free		
Internal battery charger				
Nominal input voltage		230Vac		
Nominal input frequency		50/60Hz		
Nominal voltage		219Vdc		
Max charging current	Selectable	0,7A	0,9A	1,1A
Protection				
Battery charge Input		Thermal fuse		
Battery circuit		Magnetothermic switch		
Environmental specification				
Working temperature		From 0 to 55 °C (recommended from 20 to 25 °C)		
Humidity		< 95% without condensation		
Maximum altitude		3000 m		
IP protection		IP20		
Certifications		CE		

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Easy installation



The Battery Box and Battery Pack are supplied separately in the packaging for an easy installation.

So the total weight is divided into several parts, making it easier to install.



A single operator can easily install the Battery Box inside the UPS and then the battery pack.






EASY HOT SWAP DESIGN

The innovative Design Hot Swap and the complete independence of each module allow a simple and quick maintenance and possible expansions of power and autonomy.

FLEXIBLE MODULAR DESIGN

Scalable architecture allow to easily increase power (from 20KVA to 300KVA), redundancy level (N+1 or N+X) and Back-Up time by simply additional UPS modules and Battery cabinet. All this allows to optimize the investment.



NO-DOWNTIME SYSTEM

The Redundance configuration and Hot Swap Design ensure always full power also in case of failure and replacement of module or scheduled maintenance. All this features guarantee low MTTR (Mean Time To Repair).

POWER FACTOR **1**

HIGH EFFICIENCY
96,5%

For Data Centers, Local Area Network (LAN), Industrial equipment, Electromedical equipment



- 1 10" touch LCD display
- 2 Input / Output, Maintenance Bypass, Breakers
- 3 STS Module Includes Communication Ports
- 4 Power Module
- 5 Battery Module

Ease of installation and maintenance

Built-in maintenance bypass assures continuous power to critical loads during UPS maintenance.



Easy installation and maintenance, panel control and connectors with frontal accessibility.

Find more information here



www.tecnoware.com/tec/pdf/Sch.Tec.EVO_DSP_Plus_Modular_400_ENG.pdf



FLEXIBLE BACK-UP TIME CONFIGURATION

Battery box with scalable architecture and Hot Swap design to increase Back-Up time and for easy battery maintenance.



REDUNDANT POWER SUPPLY IN STS

NO RISK OF SHUTDOWN

MODULE for UPS EVO DSP PLUS MODULAR PF1 (400Vac)		
Code	FGCEVDPM20TT	FGCEVDPM30TT
Nominal power	20kVA	30kVA
Active power	20kW	30kW
Dimensions WxHxD	44x13,2x65 cm (3U)	
Input		
Nominal Voltage	360Vac/380Vac/400Vac/415Vac (3Ph+N)	
Output		
Nominal Voltage	360Vac/380Vac/400Vac/415Vac (3Ph+N)	
Battery		
Nominal Voltage	+/- 240Vdc (12Vdc x 40 pz)	
Maximum Charging Current	6A	8A



30kVA UPS Module (400Vac)



20kVA UPS Module (400Vac)

Configuration



UPS EVO DSP PLUS MODULAR PF1 (400Vac) CABINET

Code	FGCEVDPM30B90K	FGCEVDPM30B120K	FGCEVDPM30B180K	FGCEVDPM42B120K	FGCEVDPM42B210K	FGCEVDPM42B300K
Height	30U	30U	30U	42U	42U	42U
STS Capacity	90kW	120kW	180kW	120kW	210kW	300kW
Type of installable UPS Module	30kW or 20kW					
Max. number of installable UPS Module	3	4	6	4	8	10
Battery Modules layers (4 Battery Modules each layer)	3 (12 Modules)	-	-	5 (20 Modules)	-	-
Max. capacity of installing 20kVA Module	60kW/60kVA	80kW/80kVA	120kW/120kVA	80kW/80kVA	160kW/160kVA	200kW/200kVA
Max. capacity of installing 30kVA Module	90kW/90kVA	120kW/120kVA	180kW/180kVA	120kW/120kVA	210kW/210kVA (If installed with 8 pcs, 1 is for redundancy)	300kW/300kVA

PARALLELABLE SYSTEM

Configuration



10" touch LCD display

UPS EVO DSP PLUS MODULAR PF1 (400Vac) CABINET		
Code	FGCEVDPM30A80K	FGCEVDPM30A120K
Height	30U	30U
STS Capacity	80kW	120kW
Type of installable UPS Module	20kW	200kW
Max. number of installable UPS Module	4	6
Battery Modules layers (4 Battery Modules each layer)	-	-
Max. capacity of installing HV 20kVA Module	80kW/80kVA	120kW/120kVA
		200kW/200kVA

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.






EASY HOT SWAP DESIGN

The innovative Design Hot Swap and the complete independence of each module allow a simple and quick maintenance and possible expansions of power and autonomy.

FLEXIBLE MODULAR DESIGN

Scalable architecture allow to easily increase power (from 20KVA to 140KVA), redundancy level (N+1 or N+X) and Back-Up time by simply additional UPS modules and Battery cabinet.

All this allows to optimize the investment.



NO-DOWNTIME SYSTEM

The Redundance configuration and Hot Swap Design ensure always full power also in case of failure and replacement of module or scheduled maintenance. All this features guarantee low MTTR (Mean Time To Repair).

POWER FACTOR **1**

HIGH EFFICIENCY
96,5%

For Data Centers, Local Area Network (LAN), Industrial equipment, Electromedical equipment

- 10" touch LCD display
- Compatible with Generators
- Power Factor 1
- Frequency converter
- Shared Battery Cabinet
- High MTBF and low MTTR
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.



Evo Dsp Plus Modular 208 Vac PF1

- 1 10" touch LCD display
- 2 Input/Output Switches and Maintenance Bypass
- 3 STS Module and Communication Ports
- 4 Power Module

Ease of installation and maintenance

Built-in maintenance bypass assures continuous power to critical loads during UPS maintenance.



Easy installation and maintenance, panel control and connectors with frontal accessibility.

MODULE for UPS EVO DSP PLUS MODULAR PF1 (208Vac)	
Code	FGCEDPM20TT208
Nominal power	20KVA
Active power	20KW
Dimension WxHxD	73,65x13,3x49 cm (3U)
Input	
Nominal voltage	3 x 208Vac/220Vac (3Ph+N)
Output	
Nominal voltage	3 x 208Vac/220Vac (3Ph+N)
Battery	
Nominal voltage	+/- 120Vdc (12Vdc x 20 pz)
Maximum Charging Current	8A

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

REDUNDANT
POWER SUPPLY IN STSNO RISK
OF SHUTDOWNUPS 20KVA Module
(208Vac)

PARALLELABLE SYSTEM



Configuration

UPS EVO DSP PLUS MODULAR PF1 (208Vac) CABINET			
Code	FGCEDPM30A80K208	FGCEDPM30A120K208	FGCEDPM42A140K208
Height	30U	30U	42U
STS Power	80KW	120KW	140KW
Type of installable UPS Module			
Max. number of installable UPS Module	4	6	7+1
Max. capacity of installing 20KVA Module	20-80KW/20-80KVA	20-120KW/20-120KVA	20-140KW/20-140KVA (If installed with 8 pcs, 1 is for redundancy)

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Find more information here


www.tecnoware.com/tec/pdf/Sch.Tec.EVO_DSP_PLUS_Modular_208_ENG.pdf




EASY HOT SWAP DESIGN

The innovative Design Hot Swap and the complete independence of each module allow a simple and quick maintenance and possible expansions of power and autonomy.

FLEXIBLE MODULAR DESIGN

Scalable architecture allow to easily increase power (from 70KVA to 700KVA), redundancy level (N+1 or N+X) and Back-Up time by simply additional UPS modules and Battery cabinet.

All this allows to optimize the investment.



NO-DOWNTIME SYSTEM

The Redundance configuration and Hot Swap Design ensure always full power also in case of failure and replacement of module or scheduled maintenance. All this features guarantee low MTTR (Mean Time To Repair).

POWER FACTOR **1**

HIGH EFFICIENCY
96,5%

For Data Centers, Local Area Network (LAN), Industrial equipment, Electromedical equipment

10" touch LCD display

Compatible with Generators

Power Factor 1

Frequency converter

Shared Battery Cabinet

High MTBF and low MTTR

UPS Management Software
TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.



Evo Dsp Plus Modular 480 Vac PF1
350 KW



Evo Dsp Plus Modular 480 Vac PF1
700 KW

- ① 10" touch LCD display
- ② Input/Output Switches and Maintenance Bypass
- ③ STS Module and Communication Ports
- ④ Power Module

Ease of installation and maintenance

Built-in maintenance bypass assures continuous power to critical loads during UPS maintenance.



Easy installation and maintenance, panel control and connectors with frontal accessibility.

ON LINE

EVO DSP PLUS MODULAR 480 VAC PF1


70-700

Together on



FLEXIBLE BACK-UP TIME CONFIGURATION

Battery box with scalable architecture and Hot Swap design to increase Back-Up time and for easy battery maintenance.



REDUNDANT POWER SUPPLY IN STS

NO RISK OF SHUTDOWN

MODULE for UPS EVO DSP PLUS MODULAR PF1 (480Vac)	
Code	FGCEDPM70TT480
Nominal power	70KVA
Active power	70KW
Dimension WxHxD	75x13x43,8cm (3U)
Input	
Nominal voltage	3 x 480Vac (3Ph without N)
Output	
Nominal voltage	3 x 480Vac (3Ph without N)
Battery	
Nominal voltage	+/- 240Vdc (12Vdc x 40 pz)
Maximum Charging Current	18A

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.



UPS 70KVA Module (480Vac)

PARALLELABLE SYSTEM



10" touch LCD display

Configuration

UPS EVO DSP PLUS MODULAR PF1 (480Vac) CABINET		
Code	FGCEDPM42A350K480	FGCEDPM42A700K480
Height	42U	
STS Power	350KW	700KW
Type of installable UPS Module	70KW	
Max. number of installable UPS Module	5	10
Max. capacity of installing 70KW Module	70-350KW/70-350KVA	70-700KW/70-700KVA

Find more information here



www.tecnoware.com/tec/pdf/Sch.Tec.EVO_DSP_PLUS_Modular_480_ENG.pdf





Ups Evo DSP Plus 10-20 TM PF 1

1 RS232 port 2 USB port 3 EPO connector 4 Interface for parallel connection 5 Slot for SNMP interface, Dry Contact or MODBUS 6 Input bypass switch
 7 Manual bypass switch for maintenance 8 Output voltage switch 9 Input voltage switch 10 Connector for external Battery Box 11 Input/output terminal box

DISPLAY LCD
color touch

Main Specifications

- For Local Area Network (LAN), Data Centers, Industrial equipment, Electromedical equipment
- Power factor 1
- Double input mains/bypass
- Rectifier realized by IGBT technology
- Compatible with Generators
- Battery recharge system managed by microprocessor
- Static and manual bypass
- Expandable up to 3 units in parallel with shared Box Battery
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

Specifications

UPS Model	EVO DSP PLUS TM 10.0-20.0 PF 1										
	NEW										
Code	FGCEDP10TM/00	FGCEDP10TM/C	FGCEDP10TM/D	FGCEDP10TM/E	FGCEDP10TM/2C	FGCEDP10TM/2D	FGCEDP10TM/2E	FGCEDP20TM/00	FGCEDP20TM/C	FGCEDP20TM/D	FGCEDP20TM/E
Nominal power				10 KVA					20 KVA		
Active power				10 KW					20 KW		
Power Factor								1			
Technology	On-Line Double Conversion transformerless (VFI-SS-111)										
Cooling	Fan cooling										
Dimension (UPS) WxHxD	25x82,6x63 cm										
Dimension (with packing) WxHxD	38,5x102,5x73,5 cm										
Weight	70Kg	116Kg	124Kg	128Kg	160Kg	172Kg	184Kg	80Kg	150Kg	166Kg	173Kg
Input											
Number of phases	3Ph+N										
Nominal voltage	360Vac/380Vac/400Vac/415Vac										
Nominal voltage (Ph-N)	208Vac/220Vac/230Vac/240Vac										
Input voltage range (Ph-N)	176Vac-276Vac to 100% load, 110Vac-300Vac to 50% load										
Nominal frequency	50/60 Hz										
Input frequency range On-Line mode	46-54 Hz or 56-64 Hz										
Input current harmonic distortion (THDi)	≤4%										
Input power factor	0,99										
Output											
Number of phases	1Ph+N										
Nominal voltage	208Vac/220Vac/230Vac/240Vac										
Voltage Regulation (On-Line and Battery mode)	±1%										
Voltage THD at rated linear load	<2% (linear load) - <5% (distorting load)										
Crest factor	3:1										
Frequency	50/60 Hz										
Frequency stability	±0,1 Hz										
Inverter waveform	Sinewave										
Overload capability (On-line mode)	100-110% for 60 minutes, 100-125% for 10 minutes, 125-150% for 1 minute, >150 immediate										
Overload capability (Battery mode)	100-110% for 60 minutes, 100-125% for 10 minutes, 125-150% for 1 minute, >150 immediate										
Efficiency	96%, calculated in double conversion mode at 100% load to 100% load according to standard 62040-3										
Transfer time	0 ms (On-Line)										
Battery											
Type	Lead acid, sealed, maintenance free										
Installed inside	-	20 elements (10+10)		40 elements 2 x (10+10)		-		32 elements (16+16)			
Extended autonomy	External Battery Box (opt)			-		External Battery Box (opt)		-			
Environmental specification											
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C, for longer battery life)										
Humidity	< 95% without condensation										
Maximum altitude	3000 m										
IP protection	IP20										
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)										

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Accessories

Model	Code
Parallel cables kit	FGCKITPARCA1
Internal SNMP interface	FGCNETAG7
ModBus RS485 interface	FGCMODBUS

Model	Code
Dry Contact DB9 interface	FGCEVODSDRY3
Dry Contact 9 PIN interface	FGCEVODSDRY4

**Main Specifications**

- Front door for access to battery compartments
- Removable side panels
- Isolator fuse protecting the battery circuit
- Easy maintenance

Specifications

Model	BATTERY BOX FOR EVO DSP PLUS TM 10.0 PF 1												
Code	FBBEP240A2/00	FBBEP240A2/18	FBBEP240A2/24	FBBEP240B2/00	FBBEP240B2/40	FBBEP240B2/60	FBBEP240B2/80	FBBEP240D2/00	FBBEP240D2/65	FBBEP240D2/100	FBBEP240D2/120	FBBEP240C2/00	FBBEP240C2/150
Dimension (Box) LxHxP	60 x 110 x 60 cm			61 x 140 x 68 cm			61 x 140 x 88 cm			81 x 190 x 98 cm			
Dimension (with packing) WxHxD	74 x 162,5 x 104,5 cm			94 x 212,5 x 114,5 cm			94 x 212,5 x 114,5 cm			94 x 212,5 x 114,5 cm			
Weight	80 Kg	190 kg	240 kg	175kg	420 kg	505 kg	625 Kg	175 kg	560 kg	755kg	785 Kg	285 Kg	1.155 Kg
Equipped with	Battery cable to connect UPS to Battery Box												
Battery													
Type	Lead acid, sealed, maintenance free												
Protection													
Battery circuit	Disconnector												
Environmental specification													
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)												
Humidity	< 95% without condensation												
Maximum altitude	3000 m												
IP protection	IP20												
Certifications	CE												

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

**Main Specifications**

- Front door for access to battery compartments
- Removable side panels
- Isolator fuse protecting the battery circuit
- Easy maintenance

Specifications

Model	BATTERY BOX PER EVO DSP PLUS TM 20 PF 1												
Code	FBBEP384B/00	FBBEP384B/24	FBBEP384B/40	FBBEP384C/00	FBBEP384C/60	FBBEP384C/65	FBBEP384C/80	FBBEP384D/00	FBBEP384D/100	FBBEP384D/120	FBBEP384E/00	FBBEP384E/140	FBBEP384E/200
Dimension (Box) LxHxP	61 x 140 x 88 cm			81 x 140 x 88 cm			81 x 190 x 98 cm			121 x 190 x 98 cm			
Dimension (with packing) WxHxD	74 x 162,5 x 84,5 cm			380 Kg			94 x 162,5 x 104,5 cm			94 x 212,5 x 114,5 cm			
Weight	150 Kg	380 kg	770 kg	205 kg	700 kg	820 kg	950 Kg	285 kg	1.250 kg	1.260 kg	350 Kg	1.670 kg	2.240 kg
Equipped with	Battery cable to connect UPS to Battery Box												
Battery													
Type	Lead acid, sealed, maintenance free												
Protection													
Battery circuit	Disconnector												
Environmental specification													
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)												
Humidity	< 95% without condensation												
Maximum altitude	3000 m												
IP protection	IP20												
Certifications	CE												

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.



NEW

ON LINE

UPS EVO DSP PLUS TT PF 1

10-20-30

Together on



Ups Evo DSP Plus 10-20 TT PF 1



Ups Evo DSP Plus 30 TT PF 1

1 RS232 port 2 USB port 3 EPO connector 4 Interface for parallel connection 5 Slot for SNMP interface, Dry Contact or MODBUS 6 Input bypass switch
 7 Manual bypass switch for maintenance 8 Output voltage switch 9 Input voltage switch 10 Connector for external Battery Box 11 Input/output terminal box

Main Specifications

- For Local Area Network (LAN), Data Centers, Industrial equipment, Electromedical equipment
- Power factor 1
- Double input mains/bypass
- Rectifier realized by IGBT technology
- Compatible with Generators
- Battery recharge system managed by microprocessor
- Static and manual bypass
- Expandable up to 2 units in parallel with shared Box Battery
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

**HIGH
EFFICIENCY
96%**

Specifications

UPS Model	EVO DSP PLUS TT 10.0-20.0-30.0 PF 1										NEW	NEW	NEW	NEW
Code	FGCEDP10TT/00	FGCEDP10TT/C FGCEDP10TT/2C	FGCEDP10TT/D FGCEDP10TT/2D	FGCEDP10TT/E FGCEDP10TT/2E	FGCEDP20TT/00	FGCEDP20TT/C	FGCEDP20TT/D	FGCEDP20TT/E	FGCEDP30TT/00	FGCEDP30TT/2C FGCEDP30TT/2D	FGCEDP30TT/2/2D FGCEDP30TT/2/2E			
Nominal power		10 KVA				20 KVA					30 KVA			
Active power		10 KW				20 KW					30 KW			
Power Factor							1							
Technology														
Cooling														
Dimension (UPS) WxHxD						25x82,6x63 cm								
Dimension (with packing) WxHxD						38,5x102,5x73,5 cm								
Weight	70Kg	116 Kg 160 Kg	124 Kg 176 Kg	128 Kg 184 Kg	80 Kg	150 Kg	166 Kg	173 Kg	95 Kg	235 Kg	268 Kg	280 Kg		
Input														
Number of phases														
Nominal voltage														
Nominal voltage (Ph-N)														
Input voltage range (Ph-N)														
Nominal frequency														
Input frequency range On-Line mode														
Input current harmonic distortion (THDi)														
Input power factor														
Output														
Number of phases														
Nominal voltage														
Voltage Regulation (On-Line and Battery mode)														
Voltage THD at rated linear load														
Crest factor														
Frequency														
Frequency stability														
Inverter waveform														
Overload capability (On-line mode)														
Overload capability (Battery mode)														
Efficiency														
Transfer time														
Battery														
Type														
Installed inside	-		20 elements (10+10) 40 elements 2 x (10+10)	-		32 elements (16+16)	-			64 elements (2 set 16+16)				
Extended autonomy	External Battery Box (opt)	-		External Battery Box (opt)	-		External Battery Box (opt)	-		-				
Environmental specification														
Working temperature														
Humidity														
Maximum altitude														
IP protection														
Certifications														

Accessories

Model	Code
Parallel cables kit	FGCKITPARCA1
Internal SNMP interface	FGCNETAG7
ModBus RS485 interface	FGCMODBUS
Dry Contact DB9 interface	FGCEVODSDRY3

Model	Code
Dry Contact 9 PIN interface	FGCEVODSDRY4
Three-phase isolating transf. 10 KVA star/star	FGCIT10KSST
Three-phase isolating transf. 10 KVA delta/star	FGCIT10KTST
Three-phase isolating transf. 20 KVA star/star	FGCIT20KSST

Model	Code
Three-phase isolating transf. 20 KVA delta/star	FGCIT20KTST
Three-phase isolating transf. 30 KVA delta/star	FGCIT30KSST
Three-phase isolating transf. 30 KVA delta/star	FGCIT30KTST

**Main Specifications**

- Front door for access to battery compartments
- Removable side panels
- Isolator fuse protecting the battery circuit
- Easy maintenance

Specifications

Model	BATTERY BOX FOR EVO DSP PLUS TT 10.0 PF 1												
Code	FBBEP240A2/00	FBBEP240A2/18	FBBEP240A2/24	FBBEP240B2/00	FBBEP240B2/40	FBBEP240B2/60	FBBEP240B2/80	FBBEP240D2/00	FBBEP240D2/65	FBBEP240D2/100	FBBEP240D2/120	FBBEP240C2/00	FBBEP240C2/150
Dimension (Box) LxHxP	60 x 110 x 60 cm			61 x 140 x 68 cm				61 x 140 x 88 cm				81 x 190 x 98 cm	
Dimension (with packing) WxHxD	74 x 162,5 x 104,5 cm			94 x 212,5 x 114,5 cm				94 x 212,5 x 114,5 cm				94 x 212,5 x 114,5 cm	
Weight	80 Kg	190 kg	240 kg	175kg	420 kg	505 kg	625 Kg	175 kg	560 kg	755kg	785 Kg	285 Kg	1.155 Kg
Equipped with	Battery cable to connect UPS to Battery Box												
Battery													
Type	Lead acid, sealed, maintenance free												
Protection													
Battery circuit	Disconnector												
Environmental specification													
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)												
Humidity	< 95% without condensation												
Maximum altitude	3000 m												
IP protection	IP20												
Certifications	CE												

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

**Main Specifications**

- Front door for access to battery compartments
- Removable side panels
- Isolator fuse protecting the battery circuit
- Easy maintenance

Specifications

Model	BATTERY BOX FOR EVO DSP PLUS TT 20-30 PF 1												
Code	FBBEP384B/00	FBBEP384B/24	FBBEP384B/40	FBBEP384C/00	FBBEP384C/60	FBBEP384C/65	FBBEP384C/80	FBBEP384D/00	FBBEP384D/100	FBBEP384D/120	FBBEP384E/00	FBBEP384E/140	FBBEP384E/200
Dimension (Box) LxHxP	61 x 140 x 88 cm			81 x 140 x 88 cm				81 x 190 x 98 cm				121 x 190 x 98 cm	
Dimension (with packing) WxHxD	74 x 162,5 x 84,5 cm	380 Kg		94 x 162,5 x 104,5 cm				94 x 212,5 x 114,5 cm				134x 212,5 x 114,5 cm	
Weight	150 Kg	380 kg	770 kg	205 kg	700 kg	820 kg	950 Kg	285 kg	1.250 kg	1.260 kg	350 Kg	1.670 kg	2.240 kg
Equipped with	Battery cable to connect UPS to Battery Box												
Battery													
Type	Lead acid, sealed, maintenance free												
Protection													
Battery circuit	Disconnector												
Environmental specification													
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)												
Humidity	< 95% without condensation												
Maximum altitude	3000 m												
IP protection	IP20												
Certifications	CE												

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.




NEW

ON LINE

UPS EVO DSP PLUS TT PF 1

40-60

Together on



① RS232 port ② USB port ③ EPO connector ④ Interface for parallel connection ⑤ Slot for SNMP interface, Dry Contact or MODBUS ⑥ Input bypass switch
 ⑦ Manual bypass switch for maintenance ⑧ Output voltage switch ⑨ Input switch ⑩ Connector for external Battery Box ⑪ Input/output terminal box

Main Specifications

- Local Area Networks (LAN), Data Centers, Industrial equipment, Electromedical equipment
- Power factor 1
- Double input mains/Bypass
- Rectifier realized by IGBT technology
- Compatible with Generators
- Battery charging system controlled by microprocessor
- Static and manual bypass
- Expandable up to 2 units in parallel with shared Box Battery
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

HIGH EFFICIENCY
96%



DISPLAY LCD
color touch

Specifications

UPS Model	EVO DSP PLUS TT 40.0 PF 1				EVO DSP PLUS TT 60.0 PF 1				
Code	FGCEDP40TT/00	FGCEDP40TT/2C	FGCEDP40TT/2D	FGCEDP40TT/2E	FGCEDP60TT/00				
Nominal power		40 KVA			60 KVA				
Active power		40 KW			60 KW				
Power factor									
Technology	On-Line Double Conversion transformerless (VFI-SS-111)								
Cooling	Fan cooling								
Dimension (UPS) WxHxD	30x100x81,5cm								
Dimension (with packing) WxHxD	43x123,5x95,3cm								
Weight	95 Kg	236 Kg	268 Kg	280 Kg	100 Kg				
Input	3Ph+N								
Number of phases	360Vac/380Vac/400Vac/415Vac								
Nominal voltage	208Vac/220Vac/230Vac/240Vac								
Nominal voltage (Ph-N)	176Vac-276Vac to 100% load, 110Vac-300Vac to 50% load								
Input voltage range (Ph-N)	50/60 Hz								
Nominal frequency	±7%								
Input frequency range On-Line mode	<9% to 50% load, <6% to 100% load								
Input current harmonic distortion THDi	0,99								
Input power factor									
Output	3Ph+N								
Number of phases	360Vac/380Vac/400Vac/415Vac (Ph-N: 208Vac/220Vac/230Vac/240Vac)								
Nominal voltage	±1%								
Voltage Regulation (On-Line and Battery mode)	<2% (linear load) - <5% (distorting load)								
Voltage THD at rated linear load	3:1								
Crest factor	50/60 Hz								
Frequency	±0,1 Hz								
Frequency stability	Sinewave								
Inverter waveform	100-110% for 60 minuti, 100-125% for 10 minutes, 125-150% for 1 minute, >150 immediate								
Overload capability (On-line mode)	100-110% for 60 minuti, 100-125% for 10 minutes, 125-150% for 1 minute, >150 immediate								
Overload capability (Battery mode)	96%, calculated in double conversion mode at 100% load according to standard 62040-3								
Efficiency	0 ms (On-Line)								
Transfer time									
Battery	Lead acid, sealed, maintenance free								
Type	64 elements (2 set 16+16)								
Installed inside	-								
Extended autonomy	External Battery Box (opt)	-							
Environmental specification	External Battery Box (opt)								
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)								
Humidity	< 95% without condensation								
Maximum altitude	3000 m								
IP protection	IP20								
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)								

Accessories

Model	Code
Parallel Kit	FGCKITPARCA1
Internal SNMP	FGCNETAG7
Dry Contact DB9 Interface	FGCEVODSDRY3
Dry Contact 9 PIN Interface	FGCEVODSDRY4
ModBus RS485 Interface	FGCMODBUS

Model	Code
Three-phase isolation Trans. 40 KVA star/star	FGCIT40KSST
Three-phase isolation Trans. 40 KVA delta/star	FGCIT40KTST
Three-phase isolation Trans. 60 KVA star/star	FGCIT60KSST
Three-phase isolation Trans. 60 KVA delta/star	FGCIT60KTST



TECNOManager
UPS Management Software

**Main Specifications**

- Front door for access to battery compartments
- Removable side panels
- Isolator fuse protecting the battery circuit
- Easy maintenance

Specifications

Model	BATTERY BOX FOR EVO DSP PLUS TT 40.0-60.0 PF 1									
Code	FBBEP384B/00	FBBEP384B/40	FBBEP384C/00	FBBEP384C/60	FBBEP384C/65	FBBEP384C/80				
Dimension (Box) WxHxD	61 x 140 x 68 cm			81 x 140 x 88 cm						
Dimension (with packing) WxHxD	74 x 162,5 x 84,5 cm			94 x 162,5 x 104,5 cm						
Weight	150 Kg	770 kg	205 kg	800 kg	820 kg	950 kg				
Equipped with			Battery cable to connect UPS to Battery Box							
Battery										
Type	Lead acid, sealed, maintenance free									
Protection										
Battery circuit	Disconnector									
Environmental specification										
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)									
Humidity	< 95% without condensation									
Maximum altitude	3000 m									
IP protection	IP20									
Certifications	CE									

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Specifications

Model	BATTERY BOX FOR EVO DSP PLUS TT 40.0-60.0 PF 1									
Code	FBBEP384D/00	FBBEP384D/100	FBBEP384D/120	FBBEP384E/00	FBBEP384E/140	FBBEP384E/200				
Dimension (Box) WxHxD	81 x 190 x 98 cm			121 x 190 x 98 cm						
Dimension (with packing) WxHxD	94 x 212,5 x 114,5 cm			134x 212,5 x 114,5 cm						
Weight	285 Kg	1.250 kg	1.260 kg	359 kg	1.670 kg	2.240 kg				
Equipped with			Battery cable to connect UPS to Battery Box							
Battery										
Type	Lead acid, sealed, maintenance free									
Protection										
Battery circuit	Disconnector									
Environmental specification										
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)									
Humidity	< 95% without condensation									
Maximum altitude	3000 m									
IP protection	IP20									
Certifications	CE									

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Ups Evo DSP Plus TT
80.0-100.0-120.0 PF 1Ups Evo DSP Plus TT
180.0-200.0 PF 1Ups Evo DSP Plus TT
240.0-300.0 PF 1

**EASY SWAP
INTERNAL MODULE WITH
REDUNDANT FUNCTION
(not hot swappable)**

(UPS reduces the power
if one module fails)

**POWER
FACTOR**



**POWER WALK-IN
FUNCTION**



DISPLAY LCD colour touch

**HIGH
EFFICIENCY
96%**

Main Specifications

- For Local Area Network (LAN), Data Centers, Industrial equipment, Electromedical equipment
- Touch color LCD display
- Power factor 1
- Rectifier by IGBT
- Easy Swap internal modules with redundant function (not hot swappable - UPS reduces the power if one module fails)
- Battery Recharge System managed by Microprocessor


- High compatibility with the generator: due to the Power Walk-in function, the rectifier starts up progressively, reducing the input current so no need oversize the generator.
- Modular internal structure for easy and quick maintenance
- Static and Manual Bypass
- Expandable up to 2 units in parallel
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

Specifications

UPS Model	EVO DSP PLUS TT 80.0 PF 1	EVO DSP PLUS TT 100.0 PF 1	EVO DSP PLUS TT 120.0 PF 1	EVO DSP PLUS TT 180.0 PF 1	EVO DSP PLUS TT 200.0 PF 1	EVO DSP PLUS TT 240.0 PF 1	EVO DSP PLUS TT 300.0 PF 1
Code	FGCEDP80TT/00	FGCEDP100TT/00	FGCEDP120TT/00	FGCEDP180TT/00	FGCEDP200TT/00	FGCEDP240TT/00	FGCEDP300TT/00
Nominal Power	80 KVA	100 KVA	120 KVA	180 KVA	200 KVA	240 KVA	300 KVA
Active Power	80 KW	100 KW	120 KW	180 KW	200 KW	240 KW	300 KW
Power Factor	1						
Technology	On-Line Double Conversion transformerless (VFI-SS-111)						
Cooling	Fan cooling						
Dimension (UPS) WxHxD	43x120x100 cm		60x120x100cm		60x147,5x110cm		
Weight	160 Kg	169 Kg	185 Kg	249 Kg	265 Kg	360Kg	396Kg
Input							
Number of phases	3Ph+N						
Nominal voltage	380Vac/400Vac/415Vac						
Input voltage range (Ph-N)	176Vac-276Vac to 100% load, 110Vac-300Vac to 50% load						
Nominal frequency	50/60 Hz						
Input frequency range On-Line mode	40Hz -70Hz						
Input current harmonic distortion (THDi)	≤4%						
Input power factor	0,99						
Output							
Number of phases	3Ph+N						
Nominal voltage	380Vac/400Vac/415Vac						
Voltage Regulation (On-Line and Battery mode)	±1%						
Voltage THD at rated linear load	<2% (linear load) - <4% (non-linear load)						
Crest factor	3:1						
Frequency	50/60 Hz						
Frequency stability	±0,1 Hz						
Inverter waveform	Sinewave						
Overload capability	110% for hour, 111% ~ 125% for 10 minutes, 126%~150% for 1 minute, >150% for 200 ms						
Efficiency	96%, calculated in double conversion mode at 100% load according to standard 62040-3						
Transfer time	0 ms (On-Line)						
Battery (fitted inside the external Battery Box)							
Type	Lead acid, sealed, maintenance free						
External Battery Box	See page Battery Box						
Environmental specification							
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)						
Humidity	< 95% without condensation						
Maximum altitude	3000 m						
IP protection	IP20						
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)						

Accessories

Model	Code	Model	Code
Parallel Kit for Evo Dsp Plus TT 80-300 KVA	FGCKITPAREVDP10	Three-phase isolating transformer 120 KVA star/star	FGCIT120KSST
Internal SNMP interface	FGCNETAG7	Three-phase isolating transformer 120 KVA delta/star	FGCIT120KTST
MODBUS RS485 interface	FGCMODBUS	Three-phase isolating transformer 180 KVA star/star	FGCIT180KSST
Dry Contact DB9 interface	FGCEVODSDRY3	Three-phase isolating transformer 180 KVA delta/star	FGCIT180KTST
Dry Contact 9 PIN interface	FGCEVODSDRY4	Three-phase isolating transformer 200 KVA star/star	FGCIT200KSST
Three-phase isolating transformer 80 KVA star/star	FGCIT80KSST	Three-phase isolating transformer 200 KVA delta/star	FGCIT200KTST
Three-phase isolating transformer 80 KVA delta/star	FGCIT80KTST	Three-phase isolating transformer 240 KVA star/star	FGCIT240KSST
Three-phase isolating transformer 100 KVA star/star	FGCIT100KSST	Three-phase isolating transformer 240 KVA delta/star	FGCIT240KTST
Three-phase isolating transformer 100 KVA delta/star	FGCIT100KTST	Three-phase isolating transformer 300 KVA star/star	FGCIT300KSST
		Three-phase isolating transformer 300 KVA delta/star	FGCIT300KTST

**Main Specifications**

- Front door for access to battery compartments
- Removable side panels
- Isolator fuse protecting the battery circuit
- Easy maintenance

Specifications


Model	BATTERY BOX FOR EVO DSP PLUS TT 80.0-100.0-120.0-180.0-200.0-240.0-300.0 PF 1					
Code	FBBEP384B/00	FBBEP384B/40	FBBEP384C/00	FBBEP384C/60	FBBEP384C/65	FBBEP384C/80
Dimension (Box) WxHxD	61 x 140 x 68 cm			81 x 140 x 88 cm		
Dimension (with packing) WxHxD	74 x 162,5 x 84,5 cm			94 x 162,5 x 104,5 cm		
Weight	150 Kg	770 kg	205 kg	800 kg	820 kg	950 kg
Equipped with	Battery cable to connect UPS to Battery Box					
Battery						
Type	Lead acid, sealed, maintenance free					
Protection						
Battery circuit	Disconnector					
Environmental specification						
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)					
Humidity	< 95% without condensation					
Maximum altitude	3000 m					
IP protection	IP20					
Certifications	CE					

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Specifications

Model	BATTERY BOX FOR EVO DSP PLUS TT 80.0-100.0-120.0-180.0-200.0-240.0-300.0 PF 1					
Code	FBBEP384D/00	FBBEP384D/100	FBBEP384D/120	FBBEP384E/00	FBBEP384E/140	FBBEP384E/200
Dimension (Box) WxHxD	81 x 190 x 98 cm			121 x 190 x 98 cm		
Dimension (with packing) WxHxD	94 x 212,5 x 114,5 cm			134x 212,5 x 114,5 cm		
Weight	285 Kg	1.250 kg	1.260 kg	359 kg	1.670 kg	2.240 kg
Equipped with	Battery cable to connect UPS to Battery Box					
Battery						
Type	Lead acid, sealed, maintenance free					
Protection						
Battery circuit	Disconnector					
Environmental specification						
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)					
Humidity	< 95% without condensation					
Maximum altitude	3000 m					
IP protection	IP20					
Certifications	CE					

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.



Ups Evo DSP Plus 10 TT 208V PF 1



Ups Evo DSP Plus 20 TT 208V PF 1

208 Vac

POWER FACTOR 1



DISPLAY LCD color touch

① RS232 port ② USB port ③ EPO connector ④ Interface for parallel connection ⑤ Slot for SNMP interface, Dry Contact or MODBUS ⑥ Input bypass switch
 ⑦ Manual bypass switch for maintenance ⑧ Output voltage switch ⑨ Input switch ⑩ Connector for external Battery Box ⑪ Input/output terminal box

Main Specifications

- Local Area Networks (LAN), Data Centers, Industrial equipment, Electromedical equipment
- Power factor 1
- Rectifier realized by IGBT technology
- Compatible with Generators
- Battery charging system controlled by microprocessor
- Static and manual bypass
- Expandable up to 3 units in parallel with shared Box Battery
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

HIGH EFFICENCY
94%

Specifications

UPS Model	EVO DSP PLUS 10 TT 208V PF 1	EVO DSP PLUS 20 TT 208V PF 1
Code	FGCEDP10TT208/00	FGCEDP20TT208/00
Nominal power	10 KVA	20 KVA
Active power	10 KW	20 KW
Power factor	1	
Technology	On-Line Double Conversion transformerless (VFI-SS-111)	
Cooling	Fan cooling	
Dimension (UPS) WxHxD	25x82,6x62,6cm	30x100x81,5cm
Dimension (with packing) WxHxD	38x106,1x76,4cm	43x123,5x95,3cm
Weight	45 Kg	71Kg
Input		
Number of phases	3Ph+N	
Nominal voltage	208Vac/220Vac	
Nominal voltage (Ph-N)	120Vac/127Vac	
Input voltage range (Ph-N)	88Vac-146Vac to 100% load, 70Vac-156Vac to 50% load	
Nominal frequency	50/60 Hz	
Input frequency range On-Line mode	±7%	
Input current harmonic distortion THDi	<9% to 50% load, <6% to 100% load	
Input power factor	0,99	
Output		
Number of phases	3Ph+N	
Nominal voltage	208Vac/220Vac (Ph-N: 120Vac/127Vac)	
Voltage Regulation (On-Line and Battery mode)	±1%	
Voltage THD at rated linear load	<2% (linear load) - <4% (distorting load)	
Crest factor	3:1	
Frequency	50/60 Hz	
Frequency stability	±0,1 Hz	
Inverter waveform	Sinewave	
Overload capability (On-line mode)	100-110% for 60 minutes, 100-125% for 10 minutes, 125-150% for 1 minute, >150 immediate	
Overload capability (Battery mode)	100-110% for 60 minutes, 100-125% for 10 minutes, 125-150% for 1 minute, >150 immediate	
Efficiency	94%, calculated in double conversion mode at 100% load according to standard 62040-3	
Transfer time	0 ms (On-Line)	
Battery		
Type	Lead acid, sealed, maintenance free	
Ready for installed inside	Ready for 32 elements (2 set 8+8)	
Extended autonomy	External Battery Box (optional) ±96Vdc	
Environmental specification		
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)	
Humidity	< 95% without condensation	
Maximum altitude	3000 m	
IP protection	IP20	
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)	

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Accessories

Model	Code
Parallel Kit	FGCKITPARCA1
Internal SNMP	FGCNETAG7
Dry Contact DB9 Interface	FGCEVODSDRY3
Dry Contact 9 PIN Interface	FGCEVODSDRY4
ModBus RS485 Interface	FGCMODBUS



TECNOManager

UPS Management Software

TECNOWARE®




ON LINE

UPS EVO DSP PLUS TT 208V PF 1


30-40

Together on



208 Vac

POWER FACTOR 1

DISPLAY LCD
color touch

① RS232 port ② USB port ③ EPO connector ④ Interface for parallel connection ⑤ Slot for SNMP interface, Dry Contact or MODBUS ⑥ Input bypass switch
 ⑦ Manual bypass switch for maintenance ⑧ Output voltage switch ⑨ Input switch ⑩ Input/output/ external Battery Box terminal box

Main Specifications

- Local Area Networks (LAN), Data Centers, Industrial equipment, Electromedical equipment
- Power factor 1
- Rectifier realized by IGBT technology
- Compatible with Generators
- Battery charging system controlled by microprocessor
- Static and manual bypass
- Expandable up to 3 units in parallel with shared Box Battery
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

HIGH EFFICIENCY
94%

Specifications

Modelo	EVO DSP PLUS 30 TT 208V PF 1	EVO DSP PLUS 40 TT 208V PF 1
Code	FGCEDP30TT208/00	FGCEDP40TT208/00
Nominal power	30 KVA	40 KVA
Active power	30 KW	40 KW
Power factor		
Technology	On-Line Double Conversion transformerless (VFI-SS-111)	
Cooling	Fan cooling	
Dimension (UPS) WxHxD	25x82,6x62,6cm	
Dimension (with packing) WxHxD	38x106,1x76,4cm	
Weight	112 Kg	117 Kg
Input		
Number of phases	3Ph+N	
Nominal voltage	208Vac/220Vac	
Nominal voltage (Ph-N)	120Vac/127Vac	
Input voltage range (Ph-N)	88Vac-146Vac to 100% load, 70Vac-156Vac to 50% load	
Nominal frequency	50/60 Hz	
Input frequency range On-Line mode	±7%	
Input current harmonic distortion THDi	<9% to 50% load, <6% to 100% load	
Input power factor	0,99	
Output		
Number of phases	3Ph+N	
Nominal voltage	208Vac/220Vac (Ph-N: 120Vac/127Vac)	
Voltage Regulation (On-Line and Battery mode)	±1%	
Voltage THD at rated linear load	<2% (linear load) - <4% (distorting load)	
Crest factor	3:1	
Frequency	50/60 Hz	
Frequency stability	±0,1 Hz	
Inverter waveform	Sinewave	
Overload capability (On-line mode)	100-110% for 60 minutes, 100-125% for 10 minutes, 125-150% for 1 minute, >150 immediate	
Overload capability (Battery mode)	100-110% for 60 minutes, 100-125% for 10 minutes, 125-150% for 1 minute, >150 immediate	
Efficiency	94%, calculated in double conversion mode at 100% load according to standard 62040-3	
Transfer time	0 ms (On-Line)	
Battery		
Type	Lead acid, sealed, maintenance free	
Extended autonomy	External Battery Box (optional) ±120Vdc	
Environmental specification		
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)	
Humidity	< 95% without condensation	
Maximum altitude	3000 m	
IP protection	IP20	
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)	

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Accessories

Model	Code
Parallel Kit	FGCKITPARCA1
Internal SNMP	FGCNETAG7
Dry Contact DB9 Interface	FGCEVODSDRY3
Dry Contact 9 PIN Interface	FGCEVODSDRY4
ModBus RS485 Interface	FGCMODBUS

High
Italian
Quality

TECNOWARE®





① Input switch ② Fuse breaker ③ USB Port ④ RS-232 Port ⑤ Source preference selector ⑥ Priority setting LED ⑦ Input source availability LED
 ⑧ Output source LED ⑨ Fault LED ⑩ Mute button ⑪ Slot for interface SNMP ⑫ Status Contact port ⑬ Output sockets (IEC 320 C13) ⑭ Output sockets (IEC 320 C19)
 ⑮ Input connectors (IEC 16A) ⑯ Input Terminal Block ⑰ Output Terminal Block

Main Specifications

- Powered by two separately independent power sources
- Dual power supply for redundancy
- Preferred source selection on front panel
- 19" rack design (1U)
- USB and RS232 communications ports
- UPS Management Software ATS Monitor compatible with Windows

Specifications

ATS Model	AUTOMATIC TRANSFER SWITCH 16A	AUTOMATIC TRANSFER SWITCH 30A
Code	FGCATS1601MM	FGCATS3001MM
Dimension (WxHxD)	48,3 (19") x 4,4 (1U) x 33 cm	
Weight	5 Kg	6 Kg
Communication port	USB/RS-232	
Input		
Input Voltage	230 Vac	
Input Voltage range	180 Vac - 258 Vac	
Nominal frequency	50/60 Hz	
Maximum Input Current	16A	30A
Input connectors	2 x IEC 320 C20	2 x Terminal Block
Output		
Nominal voltage	230 Vac	
Maximum Output Current	10 A for IEC 320 C13 - 16 A for IEC 320 C19	30 A for Terminal Block - 10 A for IEC 320 C13 - 16 A for IEC 320 C19
Output connectors	8 x IEC 320 C13 - 1 x IEC 320 C19	1 x Terminal Block - 4 x IEC 320 C13 - 1 x IEC 320 C19
Transfer time	9-12 ms (typical), 16 ms max	
Environmental specification		
Working temperature	From -5 to 45 °C	
Humidity	< 95% without condensation	
Certifications	CE	

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Accessories

Model	Code
Internal SNMP for ATS	FGCNETAG9



Power Battery 12V 5Ah




Power Battery 12V 7.2Ah



Power Battery 12V 9Ah



Power Battery 12V 9Ah Long Life



Power Battery 12V 54W Long Life

Main Specifications

- UPS, emergency power systems, data processing centers, alarm and security systems
- Sealed lead acid batteries
- No maintenance
- 12Vdc monoblock



- Batteries designed for regular, long and deep, discharge
- High cyclical performance
- Easy installation
- No hazardous for transport by road/rail/sea/air
- Individually packaged

SINGLE
PACKAGING


Specifications

Model	Power Battery 12V 5Ah-7.2Ah-9Ah-54W				
Code	EACPE12V05ATWB	EACPE12V7A2TWP	EACPE12V09ATWP	EACPE12V09ATWL	EACPE12V54WTWL
Box			Single packaging		
Nominal voltage	5Ah	7.2Ah	9Ah	9Ah	54W
Capacity			12Vdc		
Dimension WxHxD	90 x 101 x 70 cm			151x 94 x 65 cm	
Weight	1,65 Kg	2,22 Kg	2,65 Kg	2,87 Kg	2,87 Kg
Terminal type	Faston 6,35mm	Faston 6,35mm	Faston 6,35mm	Faston 6,35mm	Faston 6,35mm
Internal resistance	Approx 26 mΩ full charge	Approx 28 mΩ full charge	Approx 19 mΩ full charge	Approx 13 mΩ full charge	Approx 12,3 mΩ full charge
Lifespan	5 years			10 years (long life)	10 years (long life)
Container material			ABS		
Electrical Specifications					
Stand-by voltage			13,50-13,80Vdc a 25°C		
Cycle voltage			14,4-15,0Vdc a 25°C		
Initial current charging	1,25A Max	1,8A Max	2,7A Max	2,9A Max	3,7A Max
Maximum charging current		1,5A Max	2,6A Max	2,8A Max	3,5A Max
Charging time			6-8 hours		
Maximum discharge current	75A (5s)	105A (5s)	135A (5s)	140A (5s)	142 A (5s)
Environmental specification					
Working temperature			Discharge: from -15 to 50°C, Charge: from 0 to 40°C, Storage: from -15 to 40°C		
Nominal working temperature			25±3°C		
Capacity affected by temperature			40°C: 103%, 25°C: 100%, 0°C: 86%		
Certifications			CE (Regulation 1542/2023 EU)		



© 2025 Tecnoware Power Systems. The technical data may change without prior notice.





Power Battery 12V 5Ah




Power Battery 12V 7.2Ah-9Ah-54W Long Life




Power Battery 12V 54W





The communication software is downloadable free from www.tecnaware.com. Installing it on your computer can be controlled in real time, through the RS232 serial port or USB, the status of the power supply, the operation of the UPS, the charge level and the efficiency of the batteries. In the event of anomalies in the power supply, the software will automatically proceed to save all the open files and will then close down the operating system and switch off the computer in an ordered manner, before the autonomy runtime of the UPS expires. In addition, the software monitors, analyses and records a vast range of parameters related to the operation of the UPS. It visualises in real time, in the form of a graph, the input/output voltage, frequency and charge connected to the UPS, the working temperature and the charge level of the batteries.

UPS Management for Windows



UPS Management for Mac OS X



Software Compatibility

	UPS Management ¹	ATS Monitor ²
Era Plus 600-2.600	•	
Era Plus Strip 1.000	•	
Era LCD RM 1.200	•	
Era Plus Active 1.200-1.600	•	
Exa PLUS 1.100-1.600-2.100	•	
Exa PLUS 3.000-4.500	•	
Evo DSP Plus 1.200-5.500	•	
Evo DSP Plus RT 1.200-3.600	•	
Evo DSP Plus 6-10	•	
Evo DSP Plus RM 6-10	•	
Evo DSP Plus Modular 20-300	•	
Evo DSP Plus Modular 20-140	•	
Evo DSP Plus Modular 70-100	•	
Evo DSP Plus TM/TT 10-200	•	
ATS		•


1) Compatible with Windows, Mac OS X, Unix, Linux, etc

2) Compatible with Windows

SNMP Interface

(connection through RJ45 LAN network)

The SNMP (Simple Network Management Protocol) interface enables connection and configuration of the UPS in a LAN computer network. Each SNMP interface provides the necessary software for the monitoring and management of the UPS via LAN, compatible with most Operating Systems.



IP configuration



Main window




NetAgent Web Manager

SNMP Interface Compatibility

	FGCNETAG7	FGCNETAG9
Evo DSP Plus 1.200-5.500	•	
Evo DSP Plus RT 1.200-3.600	•	
Evo DSP Plus 6-10	•	
Evo DSP Plus RM 6-10	•	
Evo DSP Plus Modular 20-300	•	
Evo DSP Plus Modular 20-300	•	
Evo DSP Plus Modular 20-140	•	
Evo DSP Plus Modular 70-100	•	
Evo DSP Plus TM/TT 10-200	•	
ATS		•

Dry Contact board (Dry Contact)

Dry Contact board provides a set of relay contacts (Dry Contacts) able to identify UPS alarm status as battery mode, discharged battery, active bypass or general alarm. It can be used to interface with the systems that manage industrial processes.




Dry Contact Interface Compatibility

	FGCEVODSDRY3	FGCEVODSDRY4	STANDARD INTERFACE
Evo DSP Plus 1.200-5.500	•		
Evo DSP Plus RT 1.200-3.600	•	•	
Evo DSP Plus 6-10	•	•	
Evo DSP Plus RM 6-10	•	•	
Evo DSP Plus Modular 20-300	•	•	
Evo DSP Plus Modular 20-140	•	•	
Evo DSP Plus Modular 70-100	•	•	
Evo DSP Plus TM/TT 10-200	•	•	
ATS			•

MODBUS RS485 board

The MODBUS RS485 interface allows UPS and PC connection through MODBUS protocol. It has MODBUS RTU protocol, includes reading and writing registers and provides the RS485/RS232 interface.



MODBUS RS485 Interface Compatibility

	FGCMODBUS
Evo DSP Plus 1.200-5.500	•
Evo DSP Plus RT 1.200-3.600	•
Evo DSP Plus 6-10	•
Evo DSP Plus RM 6-10	•
Evo DSP Plus Modular 20-300	•
Evo DSP Plus Modular 20-140	•
Evo DSP Plus Modular 70-100	•
Evo DSP Plus TM/TT 10-200	•



MODBUS Manager



Stabilizer Power REG 1.000 VA

① On/Off switch ② Led AVR/Power ③ AC input cable ④ Input fuse ⑤ Stabilized output socket ⑥ RJ11 port

Main Specifications

- Domestic users, Lighting Systems, Industrial Processes, Communications, Electromedical equipment
- High stabilization speed
- High Efficiency
- No brownouts stabilization
- Do not introduce harmonic distortion
- Management changes from 0 to 100% load

Specifications

Model	STABILIZER POWER REG 1.000
Code	FSTELPRE1000M
Nominal Power	1.000 VA
Active Power	800 W
Power Factor	0,8
Technology	Electronic stabilization
Telephone / Modem Line Protection	RJ11
Dimension WxHxD	16,1x8,6x16,6 cm
Dimension (with packing) WxHxD	19,1x11,9x23,1 cm
Weight	2 Kg
Input	
Number of phases	1Ph+N
Nominal voltage	230Vac
Input voltage range	180Vac-264 Vac
Nominal frequency	50 Hz
Output	
Number of phases	1Ph+N
Nominal voltage	230Vac
Voltage regulation	±6%
Nominal frequency	50 Hz
Environmental specification	
Working temperature	From 0 to 55 °C
Humidity	< 95% without condensation
Maximum altitude	3000 m
IP protection	IP20
Certifications	CE

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.



Stabilizer Power REG 2.000 VA



Stabilizer Power REG 3.000 VA

① On/Off switch ② Input Voltage Display ③ Output Voltage Display ④ Start Up Delay time selector stabilization function: Delay 3 minutes, Undelay 10 seconds
 ⑤ Input Voltage range selector ⑥ Led Power - AVR - Overvoltage/undervoltage ⑦ AC input cable ⑧ Stabilized output socket ⑨ Input socket

Main Specifications

- Domestic users, Lighting Systems, Industrial Processes, Communications, Electromedical equipment
- High stabilization speed
- High Efficiency
- No brownouts stabilization
- Do not introduce harmonic distortion
- Management changes from 0 to 100% load

Specifications

Model	STABILIZER POWER REG 2.000-3.000	
Code	FSTELPRE2000M	FSTELPRE3000M
Nominal Power	2.000 VA	3.000 VA
Active Power	1.600 W	2.400 W
Power Factor	0.8	
Technology	Electronic stabilization	
Start Up Delay time selector stabilization function	Selectable 3 minutes-10 seconds	
Dimension WxHxD	13x18x24 cm	15x20x30 cm
Dimension (with packing) WxHxD	19x24x39 cm	23x27x33 cm
Weight	6,6Kg	8,6 Kg
Input		
Number of phases	1Ph+N	
Nominal voltage	230Vac	
Input voltage range	110Vac-280Vac o 150Vac-270Vac (selectable)	
Nominal frequency	50/60 Hz	
Output		
Number of phases	1Ph+N	
Nominal voltage	230Vac	
Voltage regulation	±6%	
Nominal frequency	50/60 Hz	
Environmental specification		
Working temperature	From 0 to 55 °C	
Humidity	< 95% without condensation	
Maximum altitude	3000 m	
IP protection	IP20	
Certifications	CE	

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.



Single-Phase from 4.5KVA
Single-Phase from 7.5KVA
Single-Phase from 10KVA



Single-Phase from 18KVA

1 Multifunction Display 2 Input voltage switch 3 Bypass switch 4 Input/output terminal box

Main Specifications

- Domestic users, Lighting Systems, Industrial Processes, Communications, Electromedical equipment
- High stabilization speed
- High Efficiency
- No brownouts stabilization
- Do not introduce harmonic distortion
- Management changes from 0 to 100% load
- Multifunction display with visualization and setting operating parameters

Specifications

Model	SERVO-ASSISTED SINGLE-PHASE STABILIZERS WITH MICROPROCESSOR ELECTRONIC CONTROL 4.5-18			
Code	FSTESM4K5M	FSTESM7K5M	FSTESM10KM	FSTESM18KM
Nominal Power	4.5 KVA	7.5 KVA	10 KVA	18 KVA
Active Power	3,6 KW	6 KW	8 KW	14.4 KW
Power Factor		0,8		
Technology	Servo-Assisted with Microprocessor Electronic Control			
Dimension WxHxD	24,3x28x34,3 cm	36x50x50 cm	30x34x40 cm	40x60x42 cm
Dimension (with packing) WxHxD				47x77x51 cm
Weight	20 Kg	24 Kg	36 Kg	80 Kg
Input				
Number of phases	1Ph+N			
Nominal voltage	220/230/240Vac (selectable)			
Input voltage range	160Vac-270Vac			
Nominal frequency	50/60 Hz			
Output				
Number of phases	1Ph+N			
Nominal voltage	220/230/240Vac (selectable)			
Voltage stability	±1%			
Voltage regulation	12 mSec/Volt			
Performance	>97%			
Load variation	From 0% to 100%			
Overload	150%			
Nominal frequency	50/60 Hz			
Environmental specification				
Working temperature	From 0 to 55 °C			
Humidity	< 95% without condensation			
Maximum altitude	3000 m			
IP protection	IP20			
Certifications	CE			

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.



Three-Phase 15KVA
Three-Phase 25KVA
Three-Phase 50KVA



Three-Phase 100KVA

① Multifunction display ② Operating status indicator ③ Input voltage switch ④ Bypass switch ⑤ Input/output terminal box

Main Specifications

- Domestic users, Lighting Systems, Industrial Processes, Communications, Electromedical equipment
- High stabilization speed
- High Efficiency
- No brownouts stabilization
- Do not introduce harmonic distortion
- Management changes from 0 to 100% load
- Multifunction display with visualization and setting the operating parameters

Specifications


Model	SERVO-ASSISTED THREE-PHASE STABILIZERS WITH MICROPROCESSOR ELECTRONIC CONTROL 15-100				
	NEW	FSTESM15KT	FSTESM25KT	FSTESM50KT	FSTESC100KT
Code					
Nominal Power		15 KVA	25 KVA	50 KVA	100 KVA
Active Power		12 KW	20 KW	40 KW	80 KW
Power Factor				0,8	
Technology		Servo-assisted with Microprocessor Electronic Control			
Dimension WxHxD		34x77x40 cm	40x85x52 cm	45x115x85 cm	52x119x86 cm
Dimension (with packing) WxHxD		39x92x48 cm	45x100x60 cm	50x130x93 cm	59x145x96 cm
Weight		92 Kg	107 Kg	157 Kg	356 Kg
Input					
Number of phases		3Ph+N			
Nominal voltage		380/400/415Vac (selectable)			
Input voltage range		260Vac-470Vac			
Nominal frequency		50/60 Hz			
Phase imbalance		100%			
Output					
Number of phases		3Ph+N			
Nominal voltage		380/400/415Vac (selectable)			
Voltage stability		±1%			
Voltage regulation		12 mSec/Volt		4 mSec/Volt	
Performance		>97%			
Load variation		From 0% to 100%			
Overload		150%			
Nominal frequency		50/60 Hz			
Environmental specification					
Working temperature		From 0 to 55 °C			
Humidity		< 95% without condensation			
Maximum altitude		3000 m			
IP protection		IP20			
Certifications		CE			

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.



Single-Phase 7.5KVA
Single-Phase 10KVA

1 Multifunction Display 2 Input voltage switch 3 Bypass switch 4 Input/output terminal box



DESIGNED FOR
PHOTOVOLTAIC SYSTEMS



Multifunction LED Display

Main Specifications

- Bidirectional, designed for Photovoltaic Systems with voltage stabilization on both mains input and output side

- For utenze domestic users, Lighting Systems
- High stabilization speed
- High Efficiency
- No brownouts stabilization

- Do not introduce harmonic distortion
- Management changes from 0 to 100% load
- Multifunction display with visualization and setting operating parameters

Specifications

Model	SERVO-ASSISTED BIDIRECTIONAL SINGLE-PHASE STABILIZERS WITH MICROPROCESSOR ELECTRONIC CONTROL 7.5-10	
Code	FSTESM7K5MBD	FSTESM10KMBD
Nominal Power	7.5 KVA	10 KVA
Active Power	6 KW	8 KW
Power Factor	0,8	
Technology	Servo-Assisted bidirectional with Microprocessor Electronic Control	
Dimension WxHxD	30x34x40 cm	
Dimension (with packing) WxHxD	36x50x50 cm	
Weight	24 Kg	36 Kg
Input		
Number of phases	1Ph+N	
Nominal voltage	220/230/240Vac (selectable)	
Input voltage range	160Vac-270Vac	
Nominal frequency	50/60 Hz	
Output		
Number of phases	1Ph+N	
Nominal voltage	220/230/240Vac (selectable)	
Voltage stability	±3%	
Voltage regulation	12 mSec/Volt	
Performance	>97%	
Load variation	From 0% to 100%	
Overload	150%	
Nominal frequency	50/60 Hz	
Environmental specification		
Working temperature	From 0 to 55 °C	
Humidity	< 95% without condensation	
Maximum altitude	3000 m	
IP protection	IP20	
Certifications	CE	

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.



**SILENT
INVERTER
Technology**

**PURE
SINEWAVE**

**ECO SPEED
CONTROL**

**EURO
GASOLINE
ENGINE**

Main Specifications

- Silent Inverter Generator
- Eco Speed Control system to optimize consumption and reduce noise
- Portable and compact
- OHV 4-stroke engine
- Pure Sinewave output voltage
- Fuel tank for 10 hours at 50% load
- Low oil alert
- Overload protection
- Battery Charger
- Dual AC and DC 12V output



Specifications

Model	SILENT INVERTER GENERATOR 2.200
Code	FGEINV2200M
Starting System	Manual
Max reactive power	2.200 VA
Max active power	2.000 W
Power factor	0,9
Rated power	1.800 W
Phase	Single Phase
Technology	Inverter
Rated voltage	230 Vac
Rated frequency	50 Hz
DC output	12Vdc - 8A
AC output	2 Schuko 16A
Insulated grade	F
Fuel	4L
Noise level at 7 m	Unleaded gasoline
Weight	58-62 dBA
Dimension WxHxD	21,5 Kg
Dimension (with packing) WxHxD	48x39x28 cm
Certifications	49x40x29cm
Engine	CE
Model	QL80
Type	Single-cylinder forcedair-cooled OHV 4-stroke
Displacement	79,7 cc
Power	6,5 HP
Rated speed	3000 RPM
Ignition system	TCI (transistor ignition)
Lubrication oil (not included)	0,35 L SAE 10W-30
Air filter type	Dry
European emission standards	Euro 5

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.





Gasoline Generator 3.200 VA Recoil Starting System



Gasoline Generator 4.200 VA Electrical Starting System



Gasoline Generator 7.800 VA Electrical Starting System



Gasoline Generator 9.200 VA Electrical/Automatic Starting System



AUTOMATIC
VOLTAGE
REGULATOR

Main Specifications

- OHV 4-stroke engine
- Metal fuel tank for 10 hours at 50% load
- Low oil alert
- AVR and overload protection
- Ready for External Automatic Transfer Switch (only for Gasoline Generator 4.200 VA and Gasoline Generator 9.200 VA)
- Battery Charger (only for electrical model)
- Dual AC and DC 12V output
- Low operation noise



Specifications

Model	GASOLINE GENERATOR 3.200-4.200-7.800-9.200 NEW				
	FGE3200M	FGE4200E	FGE4200EA	FGE7800E	FGE9200EA
Code					
Starting System	Manual	Electrical	Electrical/Automatic	Electrical	Electrical/Automatic
Max reactive power	3.200 VA	4.200 VA	4.200 VA	7.800 VA	9.200 VA
Max active power	2.200 W	3.000 W	3.000 VA	5.500 W	6.500 W
Power factor			0,7		
Rated power	2.000 W	2.800 W	2.800 W	5.000 W	6.000 W
Phase			Single Phase		
Voltage regulator			AVR		
Rated voltage			230 Vac		
Rated frequency			50 Hz		
DC output			12Vdc - 8,3A		
AC output sockets		2 Schuko 16A		2 IEC 309 16A	1 IEC 309 32A
Ready for external Gasoline Generator ATS	-		Yes - Code FGEATS9200 (optional)	-	Yes Code FGEATS9200 (optional)
Insulated grade			F		
Fuel tank capacity		15L		25L	
Fuel			Unleaded gasoline		
Noise level at 7 m		68-72 dBA			74-78 dBA
Hand rails and wheels		-			Included
Weight	41,5 Kg		48 Kg	82 Kg	85 Kg
Dimension WxHxD		43x42x63 cm			52,5x54,5x69,5 cm
Dimension (with packing) WxHxD		44x44x64 cm			53,5x56,5x70,5 cm
Certifications			CE		
Engine					
Model	TW168F		TW170F		TW188F
Type			Single-cylinder forcedair-cooled OHV 4-strok		TW190F
Displacement	196 cc		210 cc		
Power	6,5 HP		7 HP	389 cc	420 cc
Rated speed			3000 RPM	13 HP	15 HP
Ignition system			TCI (transistor ignition)		
Lubrication oil (not included)		0,6 L SAE 10W-30			1,1 L SAE 10W-30
Air filter type			A secco		
Starter battery	-		12V 7,2 Ah		12V 17 Ah
European emission standards			Euro 5		

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.

Accessories

Model	Code
External Gasoline Generator ATS for Generator FGE4200EA and FGE9200EA	FGEATS9200



1 AC mains indicator 2 Generator ON indicator 3 Automatic Starting System active indicator 4 Failure indicator 5 Manual/Automatic Starting System selector
 6 Generator Interface connector 7 Terminal Block for AC Power from Generator 8 Terminal Block for AC Power from AC mains
 9 Terminal Block for AC Power to load 10 Metal hooks for wall mounting


Main Specifications

- Metal case with hooks for wall mounting
- Metal door with key for Terminal Block access
- Generator Automatic Starting System
- Battery charger for Generator battery
- Selector for Manual/Automatic Starting
- 2m ATS/Generator connecting cable

Specifications

ATS Model	GASOLINE GENERATOR ATS 45A
Code	FGEATS9200
Dimension (WxHxD)	25x32x14 cm
Weight	4 Kg
Communication interface	Interface connector with Generator (2m cable, included)
Nominal Voltage	230 Vac
Nominal frequency	50 Hz
Maximum Current	45A
Input/Output connection	Terminal Block
Environmental specification	
Working temperature	From -5 to 45 °C
Humidity	< 95% without condensation
Certifications	CE

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.





ATA 1.200VA



ATA 3.500VA - ATA 5.500VA

POWER
FACTOR **1**

SOLAR INPUT
MPPT



Main Specifications

- Pure sinewave MPPT solar inverter
- Power Factor 1
- High PV Input Voltage Range
- Battery equalization function to optimize battery performance and extend lifecycle
- Selectable high power charging current
- Configurable AC/Solar input priority
- Compatible with generator
- Auto restart while AC is recovering
- Cold start function

Specifications

Model	ATA Solar Inverter 1.200	ATA Solar Inverter 3.500	ATA Solar Inverter 5.500		
Code	FINVATA1202	FINVATA3502	FINVATA5502		
Rated Power	1.200VA / 1.200W	3.500VA / 3.500W	5.500VA / 5.500W		
Input					
Voltage	230 VAC				
Selectable Voltage Range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)				
Frequency Range	50 Hz/60 Hz (Auto sensing)				
Output					
AC Voltage Regulation(Batt. Mode)	230VAC ± 5%				
Surge Power	2.000VA	7.000VA	11.000VA		
Efficiency (Peak)	90% ~ 93%	up to 93.5%			
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)				
Waveform	Pure sinewave				
Battery					
Battery Voltage	12 Vdc	24 Vdc	48 Vdc		
Floating Charge Voltage	13.5 Vdc	27 Vdc	54 Vdc		
Overcharge Protection	16 Vdc	33 Vdc	63 Vdc		
Solar Charger & AC Charger					
Solar Charger Type	MPPT				
Maximum PV Array Open Circuit Voltage	102 Vdc	500 Vdc			
Maximum PV Array Power	700 W	5500 W			
MPPT Range @ Operating Voltage	80~170 Vdc	120~450 Vdc			
Maximum Solar Charge Current	50 A	100 A			
Maximum AC Charge Current	20 A	80 A			
Maximum Charge Current	60 A	100 A			
Physical					
Dimension, D x W x H (mm)	103x225x320	115x300x400			
Net Weight	4.4 Kg	8.5 Kg	9 Kg		
Communication Interface	RS232	USB/RS232/Dry Contact			
Environment					
Humidity	5% to 95% Relative Humidity (Non-condensing)				
Operating Temperature	-10°C to 50°C				
Storage Temperature	-15°C to 60°C				

© 2025 Tecnoware Power Systems. The technical data may change without prior notice.



① USB communication port ② RS-232 communication port ③ AC input ④ AC output ⑤ Battery input ⑥ PV input ⑦ Circuit breaker
 ⑧ Generator dry contact ⑨ WIFI port

Hybrid Operation

With mains and photovoltaic power.



With mains power.



With photovoltaic power.



With battery power.



User Experience 4.0

Available in 10 languages, geolocation system and customer/user recognition, personalized browsing experience, dedicated commercial offer.

- E-Commerce User Oriented
- Product Registration Area
- RMA Management Area
- Tecnoware software download area

- Product Catalog with detailed technical data sheets

Configurators: a direct line between the user and our operators

People, behind your **needs**

Personal Configurator



Product Support



Tecnoware Commercial Unives

Together on

A page dedicated to the **Together On** project. Eco-friendly initiatives, virtuous information and collaboration models linked to the 10 % Eco Friendly Tecnoware philosophy, to be shared with our Partners.



Together On Products



Tecnoware Azienda Green Oriented

To be Eco-Friendly

www.tecnaware.com/togetheron



Via Montetrini 2/E 50065 Molino del Piano - Firenze - Italy

www.tecnaware.com

